

2015 SAMPLING AND ANALYSIS WORKPLAN FOR BASELINE MONITORING OF THE SOUTH FORK BLUE RIVER

PREPARED BY

Cory E. Fischer Targeted Monitoring Section

WATERSHED ASSESSMENT and PLANNING BRANCH (WAPB)
Indiana Department of Environmental Management (IDEM)
Office of Water Quality
100 North Senate Avenue
MC65-40-2 Shadeland
Indianapolis, Indiana 46204-2251

November 13, 2014

B-018-OWQ-WAP-TGM-14-W-R0

This page is intended to be blank

SIGNATURE PAGE

2015 Sampling and Analysis Workplan for Baseline Monitoring of the South Fork Blue River

Indiana Department of Environmental Management
Office of Water Quality
Watershed Assessment & Planning Branch
Indianapolis, Indiana

B-018-OWQ-WAP-TGM-14-W-R0

Reviews and Approvals

	1 . /
(2)	Date 1/6/15
Cop E. Fischer, Project Manager, Targeted Monitoring Section	
	Date <u>/////</u>
Staci Goodwin Potal Maximum Daily Load Lead, Watershed Plan	ining and Restoration Section
Kithen T Hage	Date <u>01/06/1</u> 5
Kathleen Hagan, Watershed Specialist, Watershed Planning and	Restoration Section
Timothy Bowsen	Date 1/6/2015
Timothy Bowren, Project Quality Assurance Officer, Technical and	d Logistical Services Section
	Date 1/6/2015
Chuck Bell, Section Chief, WAPB Quality Assurance Manager, T	echnical and Logistical Services Section
Stacey Sobot	Date 1/6/2015
Stacey Sobat Chief, Probabilistic Monitoring Section	
Cyndi Wag	Date 1/4/15
Cyndi [®] Wagner, Chief, Targeted Monitoring Section	7 (
Generave	Date //10/15
Marylou Renshaw, Branch Chief, Quality Assurance Coordinator, Branch	Watershed Ássessment and Planning

The IDEM Quality Improvement Section reviewed and appro	oves this Sampling and Analysis Wo	rkplan
Dav Parry	Date	
IDEM Quality Improvement Staff		

Work Plan versus QAPP:

This Sampling and Analysis Work Plan is an extension of the existing Watershed Assessment and Planning Branch, October 2004 "Quality Assurance Project Plan (QAPP) for Indiana Surface Water Quality Monitoring and Total Maximum Daily Load (TMDL) Program" and serves as a link to the existing QAPP as well as an independent QAPP of the project. Per the U.S. EPA QAPP guidance, this Work Plan establishes criteria and specifications pertaining to a specific water quality monitoring project that are usually described in the following four groups (phases) or sections as QAPP elements:

Phase A. Project Management/Planning

The plan documents project history and objectives, and establishes Data Quality Objectives (DQOs).

Phase B. Measurement/Data Acquisition

The plan describes sampling procedures, analytical methods, sample and data acquisition requirements, and the quality control measures specific to the project.

Phase C. Assessment/Oversight

The plan identifies the key elements of external and internal checks, audits, peer reviews, Data Quality Assessments (DQAs), and the preparation of Quality Assurance/Quality Control (QA/QC) Review Reports for management.

Phase D. Data Validation and Usability

The plan describes data handling and associated QA/QC activities, including QA/QC Review Reports.

Table of Contents

(QAPP Element A2)

Table of Contents

SIGNATURE PAGE	i
List of Attachments	vi
List of Figures	
LIST OF ACRONYMS	Vii
Definitions:	
Baseline Monitoring of the South Fork Blue River Watershed Objective	
I. PROJECT MANAGEMENT/PLANNING (QAPP Elements A4, A5, A6, A7, A8)	
Project/Task Organization and Schedule: (QAPP Element A4)	
Background and Project/Task Description: (QAPP Elements A5, A6)	
Data Quality Objectives (DQOs): (QAPP Element A7)	
1. State the Problem	
2. Identify the Decision	5
3. Identify the Inputs to the Decision	7
4. Define the Boundaries of the Study	8
5. Develop a Decision Rule	9
6. Specify Tolerable Limits on Decision Errors	
7. Optimize the Design for Obtaining Data	9
Training and Staffing Requirements: (QAPP Element A8)	10
II. Measurement/Data Acquisition	
Sampling Process Design/ Methods, Sample Handling and Custody	11
(QAPP Elements B1, B2, B3, B4, B5, B6, B7)	
Sampling Sites/Sampling Design: (QAPP Element B1)	
Sampling Methods and Sample Handling: (QAPP Elements B2, B3)	
Field Parameter Measurements	
Analytical Methods: (QAPP Element B4)	
Laboratory Procedure for E. coli Measurements:	
Nutrient and General Chemistry Parameters Measurements:	15
Field Parameters Measurements:	17
Quality Control and Custody Requirements: (QAPP Element B5)	17
Field Instrument Testing and Calibrations: (QAPP Elements B6, B7)	18
III. ASSESSMENT/OVERSIGHT: (QAPP Elements C1, C2)	20
Data Quality Assessment Levels	
IV. DATA VALIDATION AND USABILITY: (QAPP Element D1, D2)	
Quality Assurance/Data Qualifiers and Flags:	
Data Usability:	23
Laboratory and Estimated Cost:	
Reference Manuals and Personnel Safety:	
REFERENCES:	26
1 115 1 1 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1	٠, ٦

This page is intended to be blank

List of Attachments

Attachment 1: Modified Geometric Design Steps for Baseline Studies	
Attachment 2: IDEM Site Reconnaissance Form	
Attachment 3: Blank Stream Sampling Field Data Sheet	
Attachment 4: Fish Collection Data Sheet	
Attachment6: Biological Samples Chain-of-custody Form	
Attachment 7: Blank OWQ Biological Studies QHEI (Qualitative Habitat Evaluation Index) for	
, maoninoni i i Biank ovi a Biological Gradies and I (adamatic i labitat Evaluation indox) i c	
Attachment 8: Chain-of-custody Form	
Attachment 9: Sample Analysis Request Form	43
List of Figures	
Figure 1. South Fork Blue River Watershed Baseline Monitoring Sampling AreaFigure 2. South Fork Blue River Watershed Land Use	
List of Tables	
Table 1. Sampling Locations for Baseline Monitoring of the South Fork Blue River	
Table 2. Water Quality Criteria (327 IAC 2-1-6)	
Table 3. E. coli, Nutrient and General Chemistry Parameters Test Methods	
Table 4. Field Parameters Test Methods	
Table 5. Data Qualifiers and Flags	21

LIST OF ACRONYMS

AAC: Acute Aquatic Criterion
ADC: Acoustic Doppler Current
ADP: Acoustic Doppler Profiler
ADV: Acoustic Doppler Velocimeter

AIMS: Assessment Information Management System

CAC: Chronic Aquatic Criteria

CALM: Consolidated Assessment Listing Methodology

CCC: Criterion Continuous Concentration

CDL: Crop Data Layer

CFR: Code of Federal Regulations

CFU: Colony Forming Units

CLP: Contract Laboratory Program
COD: Chemical Oxygen Demand
ORD: Contract Laboratory Program

CPR: Cardio-Pulmonary Resuscitation

CRQL: Contract Required Quantification Limit

DO: Dissolved Oxygen

DQA: Data Quality Assessment DQO: Data Quality Objectives

E. coli: Escherichia coli

EPA: Environmental Protection Agency

GPS: Global Positioning System

HUC: Hydrologic Unit Code

IAC: Indiana Administrative Code
IBC: Impaired Biotic Community
IBI: Index of Biotic Integrity

IDEM: Indiana Department of Environmental Management

MDL: Method Detection Limit

µS/cm Micro Siemens per Centimeter

mg/L: Milligram per liter
MHAB: Multi-habitat
mL: Milliliter

MPN: Most Probable Number

MS/MSD: Matrix Spike/Matrix Spike Duplicate NTU: Nephelometric Turbidity Unit(s)

OWQ: Office of Water Quality
PFD: Personal Floatation Device
PPE: Personal Protective Equipment
QA/QC: Quality Assurance/Quality Control
QAC: Quality Assurance Coordinator
QAM: Quality Assurance Manager

QAO: Quality Assurance Officer

QAPP: Quality Assurance Project Plan

QHEI: Qualitative Habitat Evaluation Index

RFP: Request for Proposals

RL: Reporting Limit

RPD: Relative Percent Difference

S.U.: Standard Units
SM: Standard Method

SOP: Standard Operating Procedures

TDS: Total Dissolved Solids
TKN: Total Kjeldahl Nitrogen
TMDL: Total Maximum Daily Load
TOC: Total Organic Carbon
TP: Total Phosphorus

TS: Total Solids

TSS: Total Suspended Solids

U.S.: United States

USDA: United States Department of Agriculture
WAPB: Watershed Assessment and Planning Branch

Definitions:

Elutriate To purify, separate, or remove lighter or finer particles

by washing, decanting, and settling.

Geometric site Sampling site chosen according to its drainage area

within a watershed.

Fifteen (15) Minute Pick A component of the IDEM multihabitat

macroinvertebrate sampling method in which the one minute kick sample and fifty meter sweep sample collected at a site are combined, elutriated, with

macroinvertebrates removed from the resulting sample

for 15 minutes while in the field.

Fifty (50) Meter Sweep A component of the IDEM multihabitat

macroinvertebrate sampling method in which

approximately 50 meters (50m) of shoreline habitat in a stream or river is sampled with a standard 500 micrometer (500 µm) mesh width D-frame dipnet by taking 20-25 individual "jab" or "sweep" samples, which

are then composited.

One (1) minute kick sample A stationary sampling accomplished using a box

shaped net comprised of canvas bottom and/or sides and 504µ nylon mesh back. The designated area is

sampled for one minute.

Pour point The outlet of a subwatershed or the common point

where all the water flows out of any given

subwatershed.

Targeted site A sampling site intentionally selected based on specific

monitoring objectives or decisions to be made.

This page is intended to be blank

Baseline Monitoring Program Objective

Baseline Monitoring uses an intensive targeted watershed design that characterizes the current condition of an individual watershed. This type of monitoring provides valuable data for the purposes of assessment, Total Maximum Daily Load (TMDL) development, watershed planning, and allows for future comparisons to evaluate changes in the water quality within the watershed(s) studied. Selecting a spatial monitoring design with sufficient sampling density to accurately characterize water quality conditions is a critical step in the process of developing an adequate local scale watershed study.

The Indiana Department Environmental Management (IDEM) has selected the South Fork Blue River Watershed (see Figure 1, Table 1) for a water quality baseline study. Sample sites were chosen using a modified geometric site selection process as well as targeted site selection in order to get the necessary spatial representation of the entire study area. Sites within this watershed were selected based on a geometric progression of drainage areas starting with the area at the mouth of the main stem stream and working upstream through the tributaries to the headwaters. Monitoring sites were then located to the nearest bridge. A more complete description of the geometric site selection process is included as Attachment 1. Sample sites were also chosen at the nearest bridge to the pour point (the lowest point in the basin through which all water flows) of each 12 digit Hydrologic Unit Code (HUC) in the watershed, or chosen to characterize sources for TMDL development.

It is anticipated that the water quality data collected through this monitoring effort will provide the information needed to characterize the watershed for the TMDL program and local water quality managers, identify sources of impairment, designate critical areas, and enable users to make valid and informed watershed decisions. This project, by design, will also add new stream reaches for assessment of aquatic life and recreational use support and will allow for future comparisons to evaluate changes in water quality.

The draft 2014 303(d) list submitted to the U.S. EPA (IDEM 2014a) details impairments of approximately 38 miles of the South Fork Blue River Watershed in the following ways:

- Category 5(a):Impaired Biotic Community (IBC), 2.00 miles
- Category 5(a): Escherichia coli (E. coli), 31.25 miles
- Category 5(a): Dissolved Oxygen (DO), 4.38 miles

Assessment data in this watershed have been collected by IDEM from multiple programs and projects.




Figure 1. South Fork Blue River Watershed Baseline Monitoring Sampling Area¹

¹ Map site numbers refer to last two digits of site number from Table 1; e.g., 15T-010 is site 10 on map

Table 1. Sampling Locations for Baseline Monitoring of the South Fork Blue River³

Site #	AIMS Site #	Stream Name	Location	County	Latitude	Longitude
15T-001	OBS130-0002	South Fork Blue River	Fredericksburg Road	Washington	38.43444639	-86.18341847
15T-002	OBS-06-0016	South Fork Blue River	Palmyra Rd	Washington	38.44858611	-86.13521301
15T-003	OBS-06-0015	Licking Creek	Palmyra Rd	Washington	38.43741894	-86.12961261
15T-004	OBS-06-0021	Bear Creek	Wetzel Rd	Washington	38.42770392	-86.05099359
15T-005	OBS-06-0014	Bear Creek	Martinsburg Fire Rd	Washington	38.44043334	-86.05749129
15T-006	OBS-06-0013	Bear Creek	SR 135	Washington	38.46143258	-86.08194909
15T-007	OBS-06-0007	Dutch Creek	Dutch Creek Rd	Washington	38.46393356	-86.06601976
15T-008	OBS-06-0008	South Fork Blue River	SR 135	Washington	38.47850981	-86.09370001
15T-009	OBS-06-0020	South Fork Blue River	Big Springs Rd	Washington	38.4805845	-86.1130785
15T-010	OBS-06-0009	Punch Run	Shorts Corner Rd	Washington	38.50003445	-86.07901664
15T-011	OBS-06-0004	South Fork Blue River	Martinsburg Rd	Washington	38.49812761	-86.03677311
15T-012	OBS-06-0006	Tributary of South Fork Blue River	Shorts Corner Rd	Washington	38.50531258	-86.02005328
15T-013	OBS-06-0012	Tributary of South Fork Blue River	Mahuron Rd	Washington	38.50859	-86.015463
15T-014	OBS-06-0018	South Fork Blue River	Main St	Washington	38.50095172	-86.0096978
15T-015	OBS-06-0022	South Fork Blue River	Lockenour Rd	Washington	38.51238886	-85.9751927
15T-016	OBS-06-0003	Jeff Branch	E Blue River Rd	Washington	38.52409295	-85.9529973
15T-017	OBS-06-0002	South Fork Blue River	Bowers Knob Rd	Washington	38.52047971	-85.93932946
15T-018	OBS-06-0019	Jeff Branch	Bethel Rd	Washington	38.53887871	-85.95606519
15T-019	OBS-06-0011	Honey Run	North Honey Run Rd	Washington	38.52536528	-85.8982047
15T-020	OBS-06-0005	Springle Creek	Blue River Rd	Washington	38.54632127	-85.89874726
15T-021	OBS-06-0010	South Fork Blue River	Casey Hollow Rd	Washington	38.55259127	-85.88819018

³¹⁵T-### denotes that these are the selected pour points for this project

I. PROJECT MANAGEMENT/PLANNING

(QAPP Elements A4, A5, A6, A7, A8)

Project/Task Organization and Schedule: (QAPP Element A4)

The main objective of this project is to provide a comprehensive assessment of the ability of the streams in the South Fork Blue River Watershed to support aquatic life and recreational uses. Sampling for this project will begin in November 2014 and end in October 2015. Barring any hazardous weather conditions or unexpected physical barriers to accessing the site, samples will be collected for physical, chemical, bacteriological parameters, and biological communities.

Timeframes for sampling activities include:

<u>Site reconnaissance</u> activities will be completed in August 2014. Reconnaissance activities will be conducted in the office and through physical site visits.

<u>Water chemistry</u> will be sampled monthly at all sites in the watershed during the recreational season, defined as April through October in the Indiana Administrative Code (IAC, updated October 22, 2014) [327 IAC 2-1-6]. During the months of November through March, only sites at the pour point of each 12 digit HUC will be sampled monthly. The first sampling event will be conducted in November 2014 and the study will conclude in October 2015.

<u>Biological sampling</u> activities will begin in the summer of 2015 and end no later than October 16, 2015. The basin will be sampled for fish community, macroinvertebrate community, and habitat quality at all sites in the watershed. Specific dates for fish community and macroinvertebrate collections cannot be given since sampling may be postponed due to scouring of the stream substrate or in-stream cover caused by a high water event, which would result in non-representative samples.

<u>Bacteriological sampling</u> for *Escherichia coli* (*E. coli*) will take place monthly from April through October of 2015 at all sites in the watershed. In addition, *E. coli* samples will be collected five times from each site at equally spaced intervals over a 30-day period during the recreational season of April to October 2015 to determine a geometric mean.

<u>Stream flow</u> will be quantified over the sampling year at sites designated as "pour points" (Table 1) during the monthly water chemistry sampling in each 12 digit HUC. The first measurement event will be conducted in November 2014 and the study will conclude in October 2015.

Background and Project/Task Description: (QAPP Elements A5, A6)

The Baseline Monitoring program was instituted to assist in characterizing existing conditions in watersheds throughout the state. The South Fork Blue River baseline data set will be utilized by the TMDL program and shared with local watershed groups and any other interested parties. This monitoring will provide data for TMDL development and watershed planning uses and will aid in the evaluation of future changes within the basin. For this study, the following media will be used for assessment purposes: Water chemistry, stream flow, bacteriological contamination in the form of *E. coli*, fish community, macroinvertebrate assemblages, and habitat evaluations.

Data Quality Objectives (DQOs): (QAPP Element A7)

The Data Quality Objective (DQO) process (U.S. EPA 2000) is a planning tool for data collection activities. It provides a basis for balancing decision uncertainty with available resources. The DQO is required for all significant data collection efforts for a project. It is a seven-step systematic planning process used to clarify study objectives, define the appropriate types of data, and establish decision criteria on which to base the final use of the data. The DQO for the Baseline Monitoring of the South Fork Blue River is identified in the following seven steps:

1. State the Problem

Indiana is required to assess all waters of the state to determine their designated use attainment status. "Surface waters of the state are designated for full body contact recreation" and "will be capable of supporting" a "well-balanced, warm water aquatic community" [327 IAC 2-1-3]. Data from the intensive sampling of the South Fork Blue River Watershed is needed to develop a TMDL and fully characterize the current water quality condition of the watershed. This project will gather stream flow, water chemistry, bacteriological, biological (fish and macroinvertebrates), and habitat data for the purpose of assessing the designated use attainment status of the South Fork Blue River Watershed.

2. Identify the Decision

The main objective of this study is to fully assess whether the surface waters in this watershed are supporting or non-supporting for aquatic life use and recreational use, and the extent of impairment if they are non-supporting. All sites will be sampled for concentrations of physical, chemical, and biological parameters and evaluated as

"supporting" or "non-supporting" when compared with water quality criteria included below in Table 2 [327 IAC 2-1-6] following Indiana's 2014 Consolidated Assessment Listing Methodology (CALM, IDEM 2014b).

In addition to the physical, chemical, and bacteriological criteria listed in Table 2, data for several nutrient parameters will be evaluated with the benchmarks described below. Assuming a minimum of three sampling events, if two or more of the conditions below are met on the same date, the waterbody will be classified as non-supporting due to nutrients.

- Total Phosphorus (TP):
 - o one or more measurements greater than 0.3 mg/L
- Nitrogen (measured as Nitrate + Nitrite):
 - o one or more measurements greater than 10.0 mg/L
- Dissolved Oxygen (DO):
 - any measurement less than 4.0 mg/L;
 - any measurements consistently at or close to the standard, range 4.0-5.0 mg/L; or,
 - o any measurement greater than 12.0 mg/L
- pH:
 - o any measurement greater than 9.0 Standard Units (SU); or,
 - measurements consistently at or close to the standard, range 8.7-9.0 SU

Biological Criteria:

Indiana narrative biological criteria located at 327 IAC 2-1-3 states that "all waters, except as described in subdivision (5)," (i.e. limited use waters) "will be capable of supporting" a "well-balanced, warm water aquatic community." The water quality standard definition of a "well-balanced aquatic community" is "an aquatic community that: (A) is diverse in species composition; (B) contains several different trophic levels; and (C) is not composed mainly of pollution tolerant species" [327 IAC 2-1-9]. An interpretation or translation of narrative biological criteria into numeric criteria would be as follows: A stream segment is non-supporting for aquatic life use when the monitored fish or macroinvertebrate community receives an Index of Biotic Integrity (IBI) score of less than or equal to 35 which is considered "Poor" or "Very Poor" (IDEM 2014b).

Table 2. Water Quality Criteria 327 IAC 2-1-6

Parameters	Water Quality Criteria	Criterion	
E. coli	<125 MPN/100 mL	5-Sample	
April-October	<u> </u>	Geometric Mean	
(Recreational season)	≤235 MPN/100 mL	Single Sample Maximum	
Total Ammonia (NH ₃ -N)	Calculated based on pH and Temperature	Calculated CAC	
Nitrate+Nitrite-Nitrogen	≤10 mg/L	Human Health point of drinking water intake	
Dissolved Oxygen	At least 5.0 mg/L (Warm Waters)	Daily Average	
75	Not less than 4.0 mg/L at any time	Single Reading	
рН	6.0 - 9.0 S.U. except for daily fluctuations that exceed 9.0 due to photosynthetic activity	Single Reading	
Temperature	Varies Monthly	1% Annual; Maximum Limits	
Chloride	Calculated based on hardness and sulfate	Calculated CAC	

MPN = Most Probable Number, CAC = Chronic Aquatic Criterion, S.U. = Standard Units

3. Identify the Inputs to the Decision

Grab samples will be collected at the surface water sampling locations for *E. coli* and the parameters listed in Table 3. Field measurements (Table 4, page 17) will be conducted at each site during each sampling event. Visual field observations will include weather conditions, stream conditions, and percent stream canopy at each sampling location. All samples collected for bacteriological samples will be analyzed for *E. coli* using the Idexx Colilert Enzyme Substrate Standard Method SM9223B (Clesceri et al., 1998). Surface water chemistry samples will be collected monthly and processed and analyzed by the Indiana State Department of Health (ISDH) Environmental Lab using the analytical methods listed in Table 3. Stream discharge will also be measured monthly at pour points to determine total stream loadings. A fish and macroinvertebrate community sample will be collected once at each site with a corresponding habitat evaluation.

4. Define the Boundaries of the Study

The South Fork Blue River Watershed covers 126 square miles and is located primarily in Clark, Floyd, Harrison, Scott, and Washington counties. The watershed is approximately 45% forested, 29% hay/ pasture, and 20% agriculture. See Figure 2 for the South Fork Blue River Watershed 2012 land use.

See Figure 1 for the South Fork Blue River Watershed Baseline Monitoring sampling area and Table 1 for the list of sampling locations.




Figure 2. South Fork Blue River Watershed Land Use²

²United States Department of Agriculture (USDA) 2012 Crop Data Layer (CDL)

5. Develop a Decision Rule

For assessment purposes in the Indiana Integrated Report (IDEM 2014b), recreational use attainment decisions will be based on bacteriological criteria developed to protect primary contact recreational activities [327 IAC 2-1-6]. Aquatic life use support decisions will include independent evaluations of biological and chemical data as outlined in Indiana's 2014 Consolidated Assessment and Listing Methodology (CALM, IDEM 2014b).

6. Specify Tolerable Limits on Decision Errors

Sampling design error is minimized by utilizing a comprehensive checklist of informational sources, evaluation of historical information, and a thorough watershed pre-survey. This sampling design has been formulated to address data deficiencies and render the optimum amount of data needed to fill gaps in the decision process.

Good quality data are essential for minimizing decision error. By minimizing both sampling design error and measurement error for physical and biological parameters, more confidence can be placed in the conclusions drawn on the stressors and sources affecting the water quality in the study area.

Site specific aquatic life use and recreational use assessments include program specific controls to minimize the introduction of errors. These controls include: water chemistry and bacteriological blanks and duplicates, biological site revisits or duplicates, and laboratory controls through verification of species identifications. Field Procedure Manuals (IDEM 2002; OHEPA 2006) and Standard Operating Procedures (IDEM 1992b, 1992c, 1992d, 1992e, 2010a) dictate consistent and proven techniques for sample collection to assure representative samples and minimize measurement error.

The QA/QC process detects deficiencies in the data collection as set forth in the IDEM QAPP for the Indiana Surface Water Quality Monitoring Program (IDEM 2004). The QAPP requires all contract laboratories to adhere to rigorous standards during sample analyses and to provide good quality usable data. Chemists within the Watershed Assessment and Planning Branch (WAPB) review the laboratory analytical results for quality assurance. Any data which is "Rejected" due to analytical problems or errors will not be used for water quality assessment decisions. Any data flagged as "Estimated" may be used on a case-by-case basis.

7. Optimize the Design for Obtaining Data

A Modified Geometric Design (OHEPA 1999, 2012) site selection process (Attachment 1) is used in this study to get the necessary spatial representation of the entire study area. Sites within this watershed have been selected based on a geometric progression

of drainage areas and then located to the nearest bridge. Sample sites at road crossings allows for more efficient sampling of the watershed.

Training and Staffing Requirements: (QAPP Element A8)

The WAPB uses many Standard Operating Procedures (SOPs), so any new staff member must be trained by experienced IDEM professionals on how to operate field and laboratory equipment for the collection of chemical, physical, and biological parameters as well as how to perform required QA/QC procedures (information about SOPs is given in Sections II MEASUREMENT/DATA ACQUISITION and IV DATA VALIDATION and USABILITY). Before sampling starts, IDEM staff spend several days reviewing SOPs with field and laboratory personnel that may be involved with the project.

The fish or macroinvertebrate community field Crew Chief must have a Bachelor of Science degree with a concentration in biology or other closely related area and at least one year of experience with the sampling methodology and taxonomy of the aquatic communities in the region. Prior to conducting electrofishing for fish community sampling, all crew members should review the Principles and Techniques of Electrofishing correspondence course provided by the U.S. Fish & Wildlife Service, National Conservation Training Center. Field Crew Chiefs will test electrofishing equipment and conduct field training with less experienced crew members. The field Crew Chief will be responsible for completion of field data sheets, taxonomic accuracy, sampling efficiency and representation, and voucher specimen tracking.

Staff from the Technical and Logistical Services Section will assist with laboratory work requests and review laboratory data for adherence to QA/QC requirements specified in analytical test methods, contract requirements, and the IDEM QAPP for the Indiana Surface Water Quality Monitoring Program (IDEM 2004) as well as importing electronic data into the Assessment Information Management System (AIMSII) database which is used by the WAPB. The Quality Assurance Officer will create QA/QC review reports for each laboratory analysis set. Quality Assurance staff will conduct audits of field sampling procedures utilized by WAPB staff. Monitoring staff will oversee the entry of the field and laboratory data into AIMSII and perform data QA/QC for accuracy and completeness.

II. Measurement/Data Acquisition

Sampling Process Design/ Methods, Sample Handling and Custody (QAPP Elements B1, B2, B3, B4, B5, B6, B7)

Sampling Sites/Sampling Design: (QAPP Element B1)

The proposed site locations are chosen using a modified geometric and targeted design as described previously in the "Baseline Monitoring Program Objective" section of this workplan.

Site reconnaissance activities are conducted in-house and through physical site visits. In-house activities include preparation and review of site maps and aerial photographs. Physical site visits include verification of accessibility, safety considerations, equipment needed to properly sample the site, and property owner consultations, if required. All information will be recorded on the IDEM Site Reconnaissance Form (Attachment 2) and entered into the AIMS II database. Final coordinates for each site will be determined during the physical site visits or at the beginning of the sampling phase of this project using a Trimble Juno TM SB Global Positioning System (GPS), with an accuracy of one to three meters. These coordinates will be entered into the AIMS II database.

Table 1 provides a list of the selected sampling sites with the stream name, AIMS Site Number, County Name, and the latitude and longitude of each site. The map at Figure 1, paired with that table, provides a good overview of the various sampling site locations.

Sampling Methods and Sample Handling: (QAPP Elements B2, B3)

Water Chemistry

One team of two staff will collect grab water chemistry samples and record physical site observations on the stream sampling field data sheet (Attachment 3), during monthly sampling events. All water chemistry sampling will adhere to the Water Quality Surveys Section Field Procedure Manual Section 2.1 (IDEM 2002).

Bacteriological Sampling The bacteriological sampling will be conducted by one team consisting of one or two staff. Samples will be processed in an IDEM Fixed and/or Mobile *E. coli* Laboratory equipped with all materials and equipment necessary for the Colilert® Test Method. Per Element A4 Project Organization and Schedule (above), the expected time frame for bacteriological sampling will be April through October of 2015. Staff will collect the samples in a 120 mL pre-sterilized wide-mouth container from the center of flow if stream is wadeable or from the shoreline using a pole sampler if the stream is not wadeable. All samples will be consistently labeled, cooled, and held at a temperature less than 10°C during transport. All *E. coli* samples will be collected on a schedule such that any sampling crew can deliver them to the appropriate IDEM *E. coli* Laboratory for analyses within the bacteriological holding time of six hours.

The IDEM Mobile *E. coli* Laboratory is used in this project to facilitate *E. coli* testing by eliminating the necessity of transporting samples to distant contract laboratories within a six hour holding time. The IDEM Mobile *E. coli* Laboratory (Van) provides work space containing storage for samples, supplies for Colilert® Quanti-tray testing, and all equipment needed for collecting, preparing, incubating, and analyzing results in the same manner as the IDEM Fixed *E. coli* Laboratory. All supplies will be obtained from IDEXX Laboratories, Inc., Westbrook, Maine.

Fish Community Sampling

The fish community sampling will be completed by teams of three to five staff. Sampling will be performed using various standardized electrofishing methodologies depending on stream size and site accessibility. Fish assemblage assessments will be performed in a sampling reach of 15 times the length of the average wetted width, with a minimum reach of 50 meters and a maximum reach of 500 meters (Simon 1997; Simon and Dufour 1998; U.S. EPA 1995). An attempt will be made to sample all habitat types available within the sample reach to ensure adequate representation of the fish community present at the time of the sampling event. The possible list of electrofishers to be utilized include: the Smith-Root LR-24 or LR-20 Series backpack electrofishers; the Smith-Root model 1.5KVA electrofishing system; the Smith-Root model 2.5 Generator Powered Pulsator electrofisher with RCB-6B junction box and rat-tail cathode cable assembled in a canoe (if parts of the stream are not wadeable, the system may require the use of a dropper boom array outfitted in a canoe or possibly a 12 foot Loweline™ boat); or, for non-wadeable sites, the Smith-Root model 6a electrofisher assembled in a 16 foot Loweline™ boat (IDEM 1992a, 1992b, 1992c, 1992d).

Sample collections during high flow or turbid conditions will be avoided due to 1) low collection rates which result in non-representative samples and 2) safety considerations

for the sampling team. Sample collections during late autumn and seasonal cold temperatures will be avoided due to the lack of responsiveness to the electrical field by some species that can also result in samples that are not representative of the streams fish assemblage (Simon 1990; U.S. EPA 1995).

Fish will be collected using dip nets with fiberglass handles and netting of 1/8-inch bag mesh. Fish collected in the sampling reach will be sorted by species into baskets and buckets. Young-of-the year fish, less than 20 millimeters (mm) total length, will not be retained in the community sample (Simon 1990; U.S. EPA 1995).

Prior to processing fish specimens and completion of the fish collection datasheet (Attachment 4), one to two individuals per species will be preserved in 3.7% formaldehyde solution for future reference if there are more than 10 individuals for that species collected in the sampling reach, the specimens can be positively identified, and the individuals for preservation are small enough to fit in a 2000 mL jar. If however, there are few individuals captured or the specimens are too large to preserve, a photo of key characteristics will be taken for later examination. Taxonomic characteristics for possible species encountered in the basin of interest will be reviewed prior to field work. Fish specimens should also be preserved if they cannot be positively identified in the field (especially those that co-occur like the striped and common shiner), individuals that appear to be hybrids or have anomalies, as well as dead specimens that are taxonomically valuable for un-described taxa (like the new stoneroller, red shiner, or jade darter), life history studies, or research projects.

Data will be recorded for non-preserved fish on the fish collection datasheet (Attachment 4) consisting of the following: number of individuals, minimum and maximum total length in millimeters (mm), mass weight in grams (g), and number of individuals with deformities, eroded fins, lesions, tumors, and other anomalies. Once the data have been recorded, specimens will be released within the sampling reach if possible. Data will be recorded for preserved fish specimens following taxonomic identification in the laboratory.

Macroinvertebrate Sampling

The macroinvertebrate community sampling may be conducted immediately following the fish community sampling event or on a different date by crews of two to three staff. Samples are collected using a modification of the U.S. Environmental Protection Agency (EPA) Rapid Bioassessment Protocol multi-habitat (MHAB) approach using a D-frame dipnet (Barbour et al. 1999; IDEM 2010a; Klemm et al. 1990; Plafkin et al. 1989). The IDEM MHAB approach (IDEM 2010a) is composed of a 1-minute "kick" sample within a riffle or run (collected by disturbing one square meter of stream bottom substrate in a riffle or run habitat and collecting the dislodged macroinvertebrates within

the dipnet) and a 50 meter "sweep" sample of shoreline habitats (collected by disturbing habitats such as emergent vegetation, coarse particulate organic matter, depositional zones, logs and sticks and collecting the dislodged macroinvertebrates within the dipnet). The 50 meter length of riparian corridor that is sampled at each site will be defined using a rangefinder or GPS unit. If the stream is too deep to wade, a boat will be used to sample the 50 meter zone along the shoreline that has the best available habitat. The 1-minute "kick" and 50 meter "sweep" samples are combined in a bucket of water which will be elutriated through a U.S. standard number 35 (500 µm) sieve a minimum of five times so that all rocks, gravel, sand and large pieces of organic debris are removed from the sample. The remaining sample is then transferred from the sieve to a white plastic tray where the collector (while still on-site) will conduct a 15-minute pick of macroinvertebrates at a single organism rate with an effort to pick for maximum organism diversity through turning and examination of the entire sample in the tray. The resulting picked sample will be preserved in 70% isopropyl alcohol and returned to the laboratory for identification at the lowest practical taxonomic level (usually genus or species level, if possible) and evaluated using the MHAB macroinvertebrate IBI. Before leaving the site, an IDEM OWQ Macroinvertebrate Header Form (Attachment 5) will also be completed for the sample. A completed Biological Samples' chain-of- custody form (Attachment 6) accompanies the samples through the identification process.

Habitat Assessments

Habitat assessments will be completed immediately following macroinvertebrate and fish community sample collections at each site using a slightly modified version of the Ohio Environmental Protection Agency (OHEPA) Qualitative Habitat Evaluation Index (QHEI), 2006 edition (OHEPA 2006; Rankin 1995). A separate QHEI (Attachment 7) must be completed for these two media since the sampling reach length is different (i.e., 50 meters for macroinvertebrates and between 50 and 500 meters for fish).

Field Parameter Measurements

Dissolved oxygen (DO), pH, water temperature, specific conductance, and DO percent saturation will be measured with a datasonde during each sampling event, regardless of the media type being collected (IDEM 2002). Measurement procedures and operation of the datasonde shall be performed according to the manufacturers' manuals (Hydrolab Corporation 2002; YSI 2002) and Sections 2.10 − 2.13 of the Water Quality Surveys Section Field Procedure Manual (IDEM 2002). Turbidity will be measured with a Hach™ turbidity kit, and the meter number written in the comments under the field parameter measurements. If a Hach™ turbidity kit is not available, the datasonde measurement for turbidity will be recorded. All field parameter measurements will be recorded on the IDEM Stream Sampling Field Data Sheet (Attachment 3).

Flow Measurements

Flow measurements are to be taken by the water chemistry crew at the pour point sites during each sampling run using the SonTek Acoustic Doppler Profiler (ADP) at non-wadeable sites and the FlowTracker Handheld Acoustic Doppler Velocimeter (ADV)®, Ott Acoustic Digital Current (ADC), or Ott MF pro at the wadeable sites. Procedures shall be according to Section 2.6.5 of the Surveys Section Field Procedure Manual (IDEM 2002) and the manufacturers' operating manuals. (SonTek/YSI Inc 2007; 2001)

Analytical Methods: (QAPP Element B4)

Laboratory Procedure for *E. coli* **Measurements**:

At the end of each sampling run and while still in the field, water samples are processed and analyzed for *E. coli* within the six-hour holding time for collection and transportation, and the two-hour holding time for sample processing. All waters sampled are processed and analyzed for *E. coli* in the IDEM *E. coli* Mobile Laboratory or IDEM Shadeland laboratory, which is equipped with required materials and equipment necessary for the Idexx TM Colilert Test. The Colilert Test is a multiple-tube Enzyme Substrate Standard Method SM-9223 B (Clesceri et al., 1998). The *E. coli* test method and quantification limit are identified below in Table 3.

Nutrient and General Chemistry Parameters Measurements:

Nutrient and general chemistry measurement analysis is performed at ISDH Environmental Lab in accordance with pre-approved test methods and allotted time frames. The nutrient and general chemistry parameters and their respective test methods and quantification limits are identified below in Table 3. A chain-of-custody form created by the AIMS II database (Attachment 8) and a sample analysis request form (Attachment 9) accompanies each sample set through the analytical process.

Table 3. E. coli, Nutrient and General Chemistry Parameters Test Methods

Parameter	Method	Limits of Quantification	Units	Preservative	Holding Times
E. coli	SM-9223 B Enzyme Substrate Test	1.0	*MPN /100 mL	0.0008% Na ₂ S ₂ O ₃ for CL ₂	8 hours
Alkalinity (as CaCO ₃)	SM 2320B	10.0	mg/L	None	14 days
Total Solids	SM 2540B	10.0	mg/L	None	7 days
Total Suspended Solids	SM 2540D	4.0	mg/L	None	7 days
Total Dissolved Solids	SM 2540C	10.0	mg/L	None	7 days
Sulfate	EPA 300.0	.3	mg/L	None	28 days
Chloride	EPA 300.0	.25	mg/L	None	28 days
Hardness (as CaCO ₃)	SM 2340B	1.0	mg/L	HNO ₃ < pH 2	6 months
Ammonia Nitrogen	SM 4500NH3-D	0.10	mg/L	H ₂ SO ₄ < pH 2	28 days
TKN	ASTM D3590-89	0.30	mg/L	H ₂ SO ₄ < pH 2	28 days
Nitrate/Nitrite	EPA 353.2	0.05	mg/L	H ₂ SO ₄ < pH 2	28 days
Total Phosphorus	SM 4500P-E	0.05	mg/L	H ₂ SO ₄ < pH 2	28 days
TOC	SM 5310C	1.0	mg/L	H ₂ SO ₄ < pH 2	28 days
COD	EPA 410.4	10.0	mg/L	H ₂ SO ₄ < pH 2	28 days

^{*} Clesceri et al., 1998. 1 MPN = 1 CFU/100 mL

Field Parameters Measurements:

The field measurements of DO, temperature, pH, conductivity, and turbidity are taken each time a sample is collected. The field parameters and their respective test methods and sensitivity limits are identified below in Table 4.

During each sampling run, field observations from each site and ambient weather conditions at the time of sampling are noted and documented on stream sampling field data sheets (Attachment 3). Digital photos up-stream and down-stream of the sampling site will be taken, logged, and documented for later references.

Table 4. Field Parameters Test Methods

Parameter	Method	Sensitivity Limit	Units
Dissolved Oxygen (Datasonde optical)	ASTM D888-09(C)	0.01	mg/L
Dissolved Oxygen (Winkler Titration)	SM 4500-OC ¹	0.2	mg/L
Dissolved Oxygen % Saturation (Datasonde optical)	ASTM D888-09(C)	0.01	%
Turbidity (Datasonde)	SM2130B	0.02	NTU
Turbidity (Hach Turbidimeter)	EPA 180.1 ¹	0.01	NTU
Specific Conductance (Datasonde)	SM 2510B	1.0	μS/cm
Temperature (Datasonde)	SM 2550B(2)	0.1	°C
Temperature (field meter)	SM 2550B(2) ¹	0.1	°C
pH (Datasonde)	EPA 150.2	0.01	SU
pH (field meter)	SM 4500-HB ¹	0.01	SU

¹ Method used for Field Calibration Verification

Quality Control and Custody Requirements: (QAPP Element B5)

Quality assurance protocols will follow part B5 of the "Quality Assurance Project Plan for the Indiana Surface Water Quality Monitoring and Total Maximum Daily Load (TMDL) Program," Revision 3, by Timothy Bowren and Dr. Syed Ghiasuddin (IDEM 2004).

Field Instrument Testing and Calibrations: (QAPP Elements B6, B7)

The Datasonde will be calibrated immediately prior to each week's sampling (IDEM 2002). Calibration results and drift values will be recorded, maintained, stored, and archived in log books located in the calibration laboratories at the Shadeland facility. The drift value is the difference between two successive calibrations. Field parameter calibrations will conform to the procedures as described in the instrument users' manuals (Hydrolab Corporation 2002; YSI 2002). The DO component of the calibration procedure will be conducted using the air calibration method. The unit will be field checked for accuracy once during the week by comparison with a Winkler DO test, as well as Hach™ turbidity, pH, and temperature meters. Weekly calibration verification results will be recorded on the stream sampling field data sheets (Attachment 3) and entered into the AIMS II database. A Winkler DO test will also be conducted at sites where the DO concentration is 4.0 mg/L or less.

Field Analysis Data

In-situ water chemistry field data are collected in the field using calibrated or standardized equipment. Calculations may be done in the field or later at the office. Analytical results, which have limited QC checks, are included in this category. Detection limits and ranges have been set for each analysis (Table 4). Quality control checks (such as duplicate measurements, measurements of a secondary standard, or measurements using a different test method or instrument) which are performed on field or laboratory data are usable for estimating precision, accuracy, and completeness for the project.

Bacteriological Sampling

Bacteriological samples will be analyzed using the SM 9223 Enzyme Substrate Coliform Test Method, see Table 3 for quantification limits. Samples will be collected using 120 mL pre-sterilized wide-mouth containers and adhere to the six-hour holding time. Analytical results from an IDEM Fixed and/or Mobile *E. coli* Laboratory include QC check sample results from which precision, accuracy, and completeness can be determined for each batch of samples. Raw data are archived by analytical batch for easy retrieval and review. Chain-of-custody procedures must be followed, including: time of collection, time of setup, time of reading the results, and time and method of disposal (IDEM, 2002). Any method deviations will be thoroughly documented in the raw data. All QA/QC samples will be tested according to the following guidelines:

Field Duplicates will be collected at a frequency of one per batch or at least one for every 20 samples collected (≥ 5%).

Field Blank: Field Blanks will be collected at a frequency of one per batch or at

least one for every 20 samples collected (≥ 5%).

Laboratory Blank: Laboratory Blanks (sterile laboratory water blanks) will be tested at

a frequency of one per day.

Positive Control: Each lot of media will be tested for performance using *E. coli*

bacterial cultures.

Negative Controls: Each lot of media will be tested for performance using non-E. coli

and noncoliform bacterial cultures.

Water Chemistry Data

Sample bottles and preservatives used will be certified for purity by the manufacturer. Sample collection containers for each parameter, preservative and holding time (Table 3) will adhere to U.S. EPA requirements. Field duplicates and matrix spike/matrix spike duplicates (MS/MSD) shall be collected at the rate of one per sample analysis set or one per every 20 samples, whichever is greater. Additionally, field blank samples will be taken at a rate of one set per sample analysis set or one per every 20 samples, whichever is greater.

Fish Community Data

Replicate fish community sampling will be performed at a rate of 10 percent of the total fish community sites sampled, or approximately four in the basin (U.S. EPA 1995). Replicate sampling will be performed once all initial sites have been sampled, with at least two weeks of recovery between the initial and replicate sampling events. The fish community replicate sampling and habitat assessment will be performed with either a partial or complete change in field team members (U.S. EPA 1994; U.S. EPA 1995). The resulting IBI and QHEI total score between the initial visit and the revisit will be used to evaluate precision. A chain-of-custody form is used to track samples from the field to the laboratory (Attachment 6). Fish in the laboratory may be verified by regionally recognized non-IDEM freshwater fish taxonomists. All data are checked for:

- 1) completeness
- 2) calculations performed
- 3) data entered into the AIMS II database
- 4) checked again for data entry errors.

Macroinvertebrate Community Data

Replicate macroinvertebrate field samples will be collected at every 10th site. This will result in a precision evaluation based on a 10% replicate of samples collected. Records

of laboratory identifications and the QA/QC of taxonomic work is maintained by the laboratory supervisor of the Probabilistic Monitoring Section of IDEM.

III. ASSESSMENT/OVERSIGHT: (QAPP Elements C1, C2)

Field and laboratory performance and system audits will be performed to ensure good quality data. The field and laboratory performance includes precision measurements by relative percent difference of field and laboratory duplicate, accuracy measurements by percent of recovery of MS/MSD samples analyzed in the laboratory, and completeness measurements by the percent of planned samples that are actually collected, analyzed, reported, and usable for the project.

Data Quality Assessment Levels

The samples and various types of data collected by this program are intended to meet different DQA Levels as cited in the QAPP for Indiana Surface Water Quality Monitoring Program, Revision 3 (IDEM 2004). The level of Quality Assurance and the DQA Level to which the analytical data qualifies will be as follows:

- DQA Level 1 Screening Data: The results are usually generated onsite and have no QC checks. Analytical results, which are just numbers, and have no QC checks, no precision or accuracy information, and no detection limit calculations are included in this category. Onsite data are primarily used for pre-surveys and for preliminary rapid assessment.
- DQA Level 2 Field Analysis Data: Data are recorded in the field or laboratory on calibrated or standardized equipment. Field duplicates are measured on a regular periodic basis. Calculations may be done in the field or later at the office. Analytical results, which have limited QC checks, are included in this category. Detection limits and ranges have been set for each analysis. The QC checks information for field or laboratory results is useable for estimating precision, accuracy, and completeness for the project. Data from this category are used independently for rapid assessment and preliminary decisions.
- DQA Level 3 Laboratory Analytical Data: Analytical results include QC check samples for each batch of samples from which precision, accuracy, and completeness can be determined. Method detection limits (MDLs) have been determined using 40 Code of Federal Regulations (CFR) Part 136 Appendix B (CFR 2013). Additionally, all reporting information required in the laboratory contract and in the IDEM Surface Water Quality Monitoring and TMDL QAPP, especially Table

A9-1, are included in the analytical data reports. Raw data, chromatograms, spectrograms, and bench sheets are not included as part of the analytical report, but are maintained by the contract laboratory for easy retrieval and review. Data can be elevated from DQA Level 3 to DQA Level 4 by inclusion of this information in the data report and the QC data are reported using contract laboratory program (CLP) forms or CLP format. Data in this category are considered as complete, legally defensible, and used for regulatory decisions.

DQA Level 4 Enforcement Data: Analytical results mostly meet the U.S. EPA required CLP data analysis, Contract Required Quantification Limits (CRQL), and validation procedures. QC data are reported on CLP forms or CLP format. Raw data, chromatograms, spectrograms, and bench sheets are included as part of the analytical report. Additionally, all reporting information required in the laboratory contract, and in the IDEM Surface Water Quality Monitoring Program and TMDL QAPP, are included in the analytical data reports. Data falling under this category are considered as complete, legally quantitative in value, and used for regulatory decisions.

All samples collected for bacteriological and laboratory analysis for this project will adhere to DQA Level 3. All field parameters collected for this project will adhere to DQA Level 2. All of the sample data are QA/QC'd for completeness, precision, and accuracy.

IV. DATA VALIDATION AND USABILITY: (QAPP Element D1, D2)

Quality Assurance/Data Qualifiers and Flags:

The various data qualifiers and flags used for Quality Assurance and validation of the data are outlined below in Table 5.

Table 5. Data Qualifiers and Flags

Flags	Description
R	Rejected . Result is not acceptable for use in decision making processes.
J	Estimated . The use of the result in decision-making processes will be determined on a case-by-case basis.

Flags	Description
U	Between MDL and RL The result of the parameter is above the Method Detection Limit (MDL) but below the Lab Reporting Limit (RL) and will be estimated.
Q	QC Checks or Criteria One or more of the QC checks or criteria is out-of-control.
D	 RPD for Duplicates The Relative Percent Difference (RPD) for a parameter is outside the acceptable control limits. The parameter will be considered estimated or rejected on the basis listed below: 1. If the Sample or Duplicate value is less than the RL, and the other value exceeds 5 times the MDL, then the sample will be estimated. 2. If the RPD is outside the established control limits (max. RPD) but below two times the established control limits (max. RPD), then the sample will be estimated. 3. If the RPD is twice the established control limits (max. RPD) or greater, then the sample will be rejected.
В	 Blank Contamination This parameter is found in a field or a lab blank. Whether the result is accepted, estimated, or rejected will be based upon the level of contamination listed below: 1. If the result of the sample is greater than the reporting limit but less than five times the blank contamination, the result will be rejected. 2. If the result of the sample is between five and ten times the blank contamination, the result will be estimated. 3. If the result of the sample is less than the reporting limit or greater than ten times the blank contamination, the result will be accepted.
Н	 Holding Time The analysis for this parameter was performed out of the holding time. The results will be estimated or rejected on the basis listed below: 1. If the analysis was performed between the holding time limit and 1.5 times the holding time limit, the result will be estimated. 2. If the analysis was performed outside the 1.5 times the holding time limit, the result will be rejected.

Data Usability:

The environmental data collected and its usability are finally qualified and classified into one or more of the four categories: Acceptable Data, Enforcement Capable Results, Estimated Data, and Rejected Data.

- Acceptable Data are suitable for decision making and have no flagged data points.
- Enforcement Capable Results meets all QC checks and have no flagged data points.
- **Estimated Data** may be suitable for enforcement or decision making on a case by case basis.
- Rejected Data are not suitable for enforcement or for decision making.

Laboratory and Estimated Cost:

Laboratory analysis and data reporting for this project will comply with the QAPP for Indiana Surface Water Quality Monitoring and TMDL Program (IDEM/100/29/338/073/2004, see IDEM 2004), Request for Proposals (RFP) 12-48 (see IDEM 2012), and the Office of Water Quality Assessment Branch Quality Management Plan, see IDEM 2008a). Analytical tests on the general chemistry and nutrient parameters outlined in Table 3 will be performed by the ISDH Environmental Lab in Indianapolis, Indiana at no direct cost. Supplies for the bacteriological sampling will come from IDEXX Laboratories, Inc., Westbrook, Maine with a total estimated cost for this project of \$1,280. All fish and macroinvertebrate samples will be collected and analyzed by IDEM staff.

Reference Manuals and Personnel Safety:

All staff persons who participate in the field component of this study are required to have completed Basic First Aid and Cardio-Pulmonary Resuscitation (CPR) training. According to the memorandum "Change in status of Water Assessment Branch staff in accordance with the Agency training policy," dated November 29, 2010, OWQ Watershed Assessment and Planning Branch staff is exempt from initial and annual training requirements set forth in Section 6.0 of the IDEM Health and Safety Training Policy (IDEM 2010b). The memorandum also states "as an alternative to the training requirements of the policy, the WAPB will conduct in-service training at a minimum of four (4) hours per year on topics directly related to duties performed by staff." New hires or those changing job responsibilities without the minimum four-hour training must be accompanied in the field by a staff member who has met the requirements of the branch Health and Safety training.

Field personnel collecting water chemistry and bacteriological samples will follow policies and procedures established in the Surveys Section Field Procedures Manual (IDEM 2002) and the Hazardous Communication Plan Supplement (IDEM 1997). Field

personnel collecting fish and macroinvertebrate community samples must read and comply with the Biological Studies Section SOP Manual: Section II. Hazard Communications Manual (IDEM 1992e) which includes four yellow three-ring binders consisting of the:

- 1) WAPB Safety Manual;
- 2) IDEM Hazard Communications SOP;
- 3) Occupational Safety and Health Administration Handbooks;
- 4) Material Safety Data Sheets;
- 5) "Field and Laboratory Operating Procedures for use, handling and storage of chemicals in the laboratory" (Newhouse 1998a); and,
- 6) "Field and Laboratory Operating Procedures for Use, Handling, and Storage of Solutions Containing Formaldehyde" (Newhouse 1998b).

Sampling on surface waters requires safety consciousness of staff members and the use of specialized equipment; thus, staff will comply with the IDEM Personal Protective Equipment (PPE) Policy (IDEM 2008b). If an injury or illness arises in the field, staff will follow the IDEM Injury and Illness Resulting from Occupational Exposure Policy (IDEM 2010c).

Operating in and around waterbodies carries inherent risks of drowning; thus, personnel involved in sample collection will wear appropriate clothing and PPE when operating boats or sampling in deep water or swift currents. According to the memorandum "Use of Personal Flotation Devices (PFDs) by Branch Personnel," dated February 29, 2000, WAPB staff must wear U.S. Coast Guard approved Type I, II, or III PFDs whenever:

- the planned work requires them to enter the water and the maximum water depth at any portion of the work site is over their knee (note that this depth depends on the employee but it will usually be between 12 and 20 inches or 300-500 mm);
- the employee is in a watercraft of any kind that is being launched, is in the water, or is being retrieved from the water; or,
- the employee must work from structures that do not possess guard rails and are over or alongside water where the water depth is or could reasonably be expected to be three feet deep or greater.

In addition, when work is being done in boats on co-jurisdictional waters (as defined by Indiana Code (IC) 14-8-2-315) or during hours of darkness on any waters of the state, all personnel in the watercraft must wear a high intensity whistle and Safety of Life at Sea (SOLAS) certified strobe light.

Safety issues are the responsibility of all crew members; however, any questions in the field should be directed to the field crew leader. The field crew leader is responsible for the completion of all work listed in the workplan, the health and safety aspects of the sampling event, and successful interactions with landowners and members of the public.

2014 Sampling and Analysis Workplan for Baseline Monitoring of the South Fork Blue River
B-018-OWQ-WAP-TGM-14-W-R0
Date: January 6, 2015

REFERENCES:

- Barbour, M.T., J. Gerritsen, B.D. Snyder and J.B. Stribling. 1999. Rapid Bioassessment Protocols for Use in Streams and Wadeable Rivers: Periphyton, Benthic Macroinvertebrates and Fish, Second Edition. EPA/841/B-99/002. U.S. Environmental Protection Agency; Office of Water; Washington, D.C. Report available at http://water.epa.gov/scitech/monitoring/rsl/bioassessment/
- Clesceri, L.S., Greenburg, A.E., Eaton, A.D., 1998. SM-Standards Methods for the Examination of Water and Wastewater 20th Edition. American Public Health Association.
- Code of Federal Regulations (CFR). 40 CFR Part 136, Appendix B Revised March 12, 2007. Available at http://www.gpo.gov/fdsys/pkg/CFR-2012-title40-vol24/pdf/CFR-2012-title40-vol24-part136-appB.pdf
- Hydrolab Corporation. 2002, revision c. Quanta Water Quality Monitoring System Operating Manual. Loveland, Colorado. Available at http://www.hachhydromet.com/web/ott_hach.nsf/id/pa_users_manuals_e.html
- IAC(Indiana Administrative Code), Title 327 Water Pollution Control Division, Article 2. Water Quality Standards. Last updated October 22, 2014. Available at http://www.in.gov/legislative/iac/iac_title?iact=327
- IDEM. 1992a, revision 1. Section 3, Quality Assurance Project Plan, Development of Biological Criteria (Fish) for the Ecoregions of Indiana. Biological Studies Section, Surveillance and Standards Branch, Office of Water Management, Indiana Department of Environmental Management, Indianapolis, Indiana.
- IDEM. 1992b, revision 1. Section 4, Standard Operating Procedures for Fish Collections, Use of Seines, Electrofishers, and Sample Processing. Biological Studies Section, Surveillance and Standards Branch, Office of Water Management, Indiana Department of Environmental Management, Indianapolis, Indiana.
- IDEM. 1992c, revision 1. Section 5, Standard Operating Procedures for Conducting Rapid Assessment of Ambient Water Quality Using Fish (RBP-V). Biological Studies Section, Surveillance and Standards Branch, Office of Water Management, Indiana Department of Environmental Management, Indianapolis, Indiana.
- IDEM. 1992d, revision 1. Section 11, Standard Operating Procedures-Appendices of Operational Equipment Manuals and Procedures. Biological Studies Section, Surveillance and Standards Branch, Office of Water Management, Indiana Department of Environmental Management, Indianapolis, Indiana.
- IDEM. 1992e, revision 1. Section 2, Biological Studies Section Hazards Communications Manual (List of Contents). Biological Studies Section, Surveillance and Standards Branch, Office of Water Management, Indiana Department of Environmental Management, Indianapolis, Indiana. (This Manual is not available in

- electronic format but may be inspected at the Watershed and Assessment Branch offices at 2525 North Shadeland, Indianapolis, IN.)
- IDEM. 1997. Water Quality Surveys Section Laboratory and Field Hazard Communication Plan Supplement. IDEM 032/02/018/1998, Revised October 1998. Assessment Branch, Indiana Department of Environmental Management, Indianapolis, Indiana
- IDEM. 2002. Water Quality Surveys Section Field Procedure Manual, Assessment Branch, Indiana Department of Environmental Management, Indianapolis, Indiana. IDEM, April 2002.
- IDEM. 2004. Quality Assurance Project Plan (QAPP) for Indiana Surface Water Quality Monitoring and Total Maximum Daily Load (TMDL) Program, (Rev. 3, Oct. 2004).
- IDEM. 2008a. Office of Water Quality Assessment Branch Quality Management Plan, Revision 0. B-001-OWQ-A-00-08-R00. Assessment Branch, Office of Water Quality, Indiana Department of Environmental Management, Indianapolis, Indiana.
- IDEM. 2008b. IDEM Personal Protective Equipment Policy, revised May 1 2008. A-059-OEA-08-P-R0. Office of External Affairs, Indiana Department of Environmental Management, Indianapolis, Indiana.
- IDEM. 2010a. Multi-habitat (MHAB) Macroinvertebrate Collection Technical Standard Operating Procedure. S-001-OWQ-W-BS-10-T-R0. Watershed Planning and Assessment Branch, Office of Water Quality, Indiana Department of Environmental Management, Indianapolis, Indiana.
- IDEM. 2010b. IDEM Health and Safety Training Policy, revised October 1 2010. A-030-OEA-10-P-R2.Office of External Affairs, Indiana Department of Environmental Management, Indianapolis, Indiana.
- IDEM. 2010c. IDEM Injury and Illness Resulting from Occupational Exposure Policy, revised October 1 2010. A-034-OEA-10-P-R2. Office of External Affairs, Indiana Department of Environmental Management, Indianapolis, Indiana
- IDEM. 2012c. Quality Management Plan. Indiana Department of Environmental Management. Office of Water Quality. Indianapolis, IN.
- IDEM. 2014a. Draft 2014 303(d) List Submitted to U.S. EPA on April 1, 2014. Edited by Jody Arthur. Office of Water Quality, Indiana Department of Environmental Management, Indianapolis, Indiana. Available at http://www.in.gov/idem/nps/2647.htm
- IDEM. 2014b. Indiana's 2014 Consolidated Assessment and Listing Methodology (CALM) Revised. Edited by Jody Arthur. Office of Water Quality, Indiana Department of Environmental Management, Indianapolis, Indiana. Available at http://www.in.gov/idem/nps/files/ir_2014_report_apndx_h_calm.pdf

- Klemm, D.J., P.A. Lewis, F.Fulk and J.M. Lazorchak. 1990. Macroinvertebrate Field and Laboratory Methods for Evaluating the Biological Integrity of Surface Waters. EPA/600/4-90/030. Environmental Monitoring Systems Laboratory, Monitoring Systems and Quality Assurance, Office of Research and Development, U.S. Environmental Protection Agency, Cincinnati, Ohio.
- Newhouse, S.A. 1998a. Field and laboratory operating procedures for use, handling and storage of chemicals in the laboratory. IDEM/32/03/007/1998. Biological Studies Section, Assessment Branch, Office of Water Management, Indiana Department of Environmental Management, Indianapolis, Indiana.
- Newhouse, S.A. 1998b. Field and laboratory operating procedures for use, handling and storage of solutions containing formaldehyde. IDEM/32/03/006/1998. Biological Studies Section, Assessment Branch, Office of Water Management, Indiana Department of Environmental Management, Indianapolis, Indiana.
- Ohio Environmental Protection Agency (OHEPA). 1999. Ohio EPA Five-Year Surface Water Monitoring Strategy: 2000 2004. Ohio EPA Technical Bulletin MAS/1999-7-2. Division of Surface Water, Lazarus Government Center, 211 S. Front Street, Columbus, Ohio 43215. Page 70. Report available at: http://www.epa.gov/nheerl/arm/documents/ohiofiveyearmonitstratdraft.pdf
- Ohio Environmental Protection Agency (OHEPA). 2006. Methods for Assessing Habitat in Flowing Waters: Using the Qualitative Habitat Evaluation Index (QHEI). OHIO EPA Technical Bulletin EAS/2006-06-1. Revised by the Midwest Biodiversity Institute for State of Ohio Environmental Protection Agency, Division of Surface Water, Ecological Assessment Section, Groveport, Ohio. Report available at http://www.epa.state.oh.us/portals/35/documents/gheimanualjune2006.pdf
- Ohio Environmental Protection Agency (OHEPA). 2012. 2011 Biological and Water Quality Study of Mill Creek and Tributaries, Hamilton County, Ohio. Technical Report MBI/2012-6-10. MSD Project Number 10180900. Prepared for: Metropolitan Sewer District of Greater Cincinnati, 1081 Woodrow Street, Cincinnati, OH 45204. Submitted by: Midwest Biodiversity Institute, P.O. Box 21561, Columbus, Ohio 43221-0561. Pages 40-1. Report available at: http://projectgroundwork.org/downloads/reports/2011_mill_creek_biological_water_quali
- Plafkin, J.L., M.T. Barbour, K.D. Porter, S.K. Gross and R.M. Hughes. 1989. Rapid Bioassessment Protocols for Use in Streams and Rivers: Benthic Macroinvertebrates and Fish. EPA/440/4-89/001. Assessment and Watershed Protection Division, U.S. Environmental Protection Agency, Washington, D.C. Report available at

ty study.pdf

http://nepis.epa.gov/Exe/ZyNET.exe/9100LGCA.TXT?ZyActionD=ZyDocument&Client=EPA&Index=1986+Thru+1990&Docs=&Query=&Time=&EndTime=&SearchMethod=1&TocRestrict=n&Toc=&TocEntry=&QField=&QFieldYear=&QFieldMonth=&QFieldDay=&IntQFieldOp=0&ExtQFieldOp=0&XmlQuery=&File=D%3A%5Czyfiles%5Clndex%20Data%5C86thru90%5CTxt%5C00000022%5C9100LGCA.txt&User=ANONYMOUS&Password=anonymous&SortMethod=h%7C-

- &MaximumDocuments=1&FuzzyDegree=0&ImageQuality=r75g8/r75g8/x150y150g1 6/i425&Display=p%7Cf&DefSeekPage=x&SearchBack=ZyActionL&Back=ZyActionS &BackDesc=Results%20page&MaximumPages=1&ZyEntry=1&SeekPage=x&ZyPU RL
- Rankin, E.T. 1995. Habitat Indices in Water Resource Quality Assessments. pp. 181-208, Chapter 13, Biological Assessment and Criteria: Tools for the Risk-based Planning and Decision Making, edited by Wayne S. Davis and Thomas P. Simon, Lewis Publishers, Boca Raton, Florida.
- Simon, T.P. 1990. Quality Assurance Program Plan: Development of Biological Criteria for the Ecoregions of Indiana. Region V, Environmental Sciences Division, Central Regional Laboratory, Organic Chemistry Section: Biology Team, U.S. Environmental Protection Agency, Chicago, Illinois.
- Simon, T.P. 1997. Biological Characterization of the Middle Fork Anderson River, Perry County, Indiana. EPA 905/R-96/007. Water Division, Watershed and Non-Point Branch, U.S. Environmental Protection Agency, Region V, Chicago. Illinois.
- Simon, T.P. and R.L. Dufour. 1998. Development of Index of Biotic Integrity
 Expectations for the Ecoregions of Indiana V: Eastern Cornbelt Plain. EPA 905/R-96/004. Water Division, Watershed and Non-Point Branch, U.S. Environmental Protection Agency Region V, Chicago, Illinois. Report available at <a href="http://nepis.epa.gov/Exe/ZyNET.exe/2000BST2.TXT?ZyActionD=ZyDocument&Client=EPA&Index=1995+Thru+1999&Docs=&Query=&Time=&EndTime=&SearchMethod=1&TocRestrict=n&Toc=&TocEntry=&QField=&QFieldYear=&QFieldMonth=&QFieldDay=&IntQFieldOp=0&ExtQFieldOp=0&XmlQuery=&File=D%3A%5Czyfiles%5CIndex%20Data%5C95thru99%5CTxt%5C00000006%5C2000BST2.txt&User=ANONYMOUS&Password=anonymous&SortMethod=h%7C-&MaximumDocuments=1&FuzzyDegree=0&ImageQuality=r75g8/r75g8/x150y150g16/i425&Display=p%7Cf&DefSeekPage=x&SearchBack=ZyActionL&Back=ZyActionS&BackDesc=Results%20page&MaximumPages=1&ZyEntry=1&SeekPage=x&ZyPURL
- Simon, T.P. and R.L. Dufour. 2005. Guide to appropriate metric selection for calculating the Index of Biotic Integrity (IBI) for Indiana Large and Great Rivers, Inland Lakes, and Great Lakes nearshore. U.S. Department of the Interior, Fish and Wildlife Service, Bloomington Field Office, Bloomington, Indiana.
- SonTek/YSI Inc 2001, SonTek/YSI ADP® Acoustic Doppler Profiler Technical Documentation. 2001. Available at http://www.sontek.com/adp-adcp.php
- SonTek/YSI Inc 2007, FlowTrackers® User's Manual. 2007. Available at http://www.sontek.com/flowtracker.php
- United States Environmental Protection Agency (U.S. EPA). March 1994.
 Environmental Monitoring and Assessment Program, Surface Waters and Region 3
 Regional Environmental Monitoring and Assessment Program, 1994 Pilot Field
 Operations and Methods Manuals for Streams. EPA/620/R-94/004F. Edited by

Donald J. Klemm and James M. Lazorchak. Bioassessment and Ecotoxicology Branch, Ecological Monitoring Research Division, Environmental Monitoring Systems Laboratory, U.S. Environmental Protection Agency, Cincinnati, Ohio. Report available at

http://www.epa.gov/emap2/html/pubs/docs/groupdocs/surfwatr/field/ws_abs.html

- U.S. EPA 1995, Region 5 R-EMAP Full Proposal: Spatial Evaluation of the Eastern Corn Belt Plain Rivers and Streams for the Development of Reference Condition using EMAP Sampling Design and Indicators, with Comparison of Results to Nonrandom Intensive.
- U.S. EPA, 2000. Guidance for the Data Quality Objectives Process. EPA QA/G-4. EPA/600/R-96/055, August 2000. Report available at http://www.epa.gov/region6/qa/qadevtools/mod4references/secondaryguidance/g4-final.pdf
- YSI Incorporated. 2002, revision b. 6-Series Environmental Monitoring Systems Manual, Yellow Springs, Ohio. Available at http://www.ysi.com/mwg-internal/de5fs23hu73ds/progress?id=fdaTJVUSbg

DISTRIBUTION LIST:

Electronic Distribution Only: (QAPP Element A3)

<u>Name</u>	<u>Organization</u>
Tim Beckman	IDEM/OWQ/ Watershed Assessment and Planning Branch / Targeted Monitoring Section
Cyndi Wagner	IDEM/OWQ/ Watershed Assessment and Planning Branch / Targeted Monitoring Section
Paul McMurray	IDEM/OWQ/ Watershed Assessment and Planning Branch /Probabilistic Monitoring Section
Stacey Sobat	IDEM/OWQ/ Watershed Assessment and Planning Branch /Probabilistic Monitoring Section
Kathleen Hagan	IDEM/OWQ/ Watershed Assessment and Planning Branch /Watershed Planning and Restoration Section
Staci Goodwin	IDEM/OWQ/ Watershed Assessment and Planning Branch /Watershed Planning and Restoration Section
Bonny Elifritz	IDEM/OWQ/ Watershed Assessment and Planning Branch /Watershed Planning and Restoration Section
Timothy Bowren	IDEM/OWQ/ Watershed Assessment and Planning Branch /Technical and Logistics Section
Chuck Bell	IDEM/OWQ/ Watershed Assessment and Planning Branch /Technical and Logistics Section
Jody Arthur	IDEM/OWQ/ Watershed Assessment and Planning Branch /Technical E7
Marylou Renshaw	IDEM/OWQ/ Watershed Assessment and Planning Branch
Dav Parry	IDEM/ Office of Compliance Support/Planning and Assessment/ Quality Improvement Section
Michael Spinar	IDEM/ Office of Compliance Support/Planning and Assessment/ Quality Improvement Section

Attachment 1: Modified Geometric Design Steps for Baseline Studies

Introduction

A relatively new design that has recently been implemented in Indiana is termed the Geometric Site Selection process. This design is employed within watersheds that correspond to the 12-14 digit HUC scale in order to fulfill multiple water quality management objectives, not just the conventional focus on status assessment. It is employed at a spatial scale that is representative of the scale at which watershed management is generally being conducted.

Sites within the watershed are allocated based on a geometric progression of drainage areas starting with the area at the mouth of the main stem river or stream (pour point) and working "upwards" through the various tributaries to the primary headwaters. This approach allocates sampling sites in a semi-random fashion and according to the stratification of available stream and river sizes based on drainage area. The Geometric Site Selection process is then modified by adding a targeted selection of additional sampling sites that are used to focus on localized management issues such as point source discharges, habitat modifications, and other potential impacts within a watershed. These sites are then "snapped to bridges" to facilitate safe and easy access to the stream. This design also fosters data analysis that takes into consideration overlying natural and human caused influences within the streams of a watershed. The design has been particularly useful for watersheds that are targeted for TMDL development because missing, incomplete, or outdated assessments can be addressed prior to TMDL development.

Selection Process

In ArcGIS, download from NHD Plus site (http://www.horizon-systems.com/nhdplus/HSC-wthMS.php) the following files for Region 5 (and then again for Region 7) and zip them into the appropriate file structure.

File Description	File Name (.zip***)	Format
Region 05, Version 01_01, Catchment Grid	NHDPlus05V01_01_Catgrid	ESRI Grid
Region 05, Version 01_01, Catchment Shapefile	NHDPlus05V01_01_Catshape	Shapefile
Region 05, Version 01_02, Catchment Flowline Attributes	NHDPlus05V01_02_Cat_Flowline_Attr	DBF
Region 05, Version 01_02, Elevation Unit a	NHDPlus05V01_02_Elev_Unit_a	ESRI Grid
Region 05, Version 01_02, Elevation Unit b	NHDPlus05V01_02_Elev_Unit_b	ESRI Grid
Region 05, Version 01_02, Elevation Unit c	NHDPlus05V01_02_Elev_Unit_c	ESRI Grid
Region 05, Version 01_01, Flow Accumulation and Flow Direction Unit a	NHDPlus05V01_01_FAC_FDR_Unit_a	ESRI Grid
Region 05, Version 01_01, Flow Accumulation and Flow Direction Unit b	NHDPlus05V01_01_FAC_FDR_Unit_b	ESRI Grid
Region 05, Version 01_01, Flow Accumulation and Flow Direction Unit c	NHDPlus05V01_01_FAC_FDR_Unit_c	ESRI Grid
Region 05, Version 01_02, National Hydrography Dataset	NHDPlus05V01_03_NHD	Shapefile and DBF
Region 05, Version 01_01, Stream Gage Events	NHDPlus05V01_01_StreamGageEvent	Shapefile
Region 05, Version 01_01, QAQC Sinks Spreadsheet	NHDPlus05V01_01_QAQC_Sinks	Excel Spreadsheet

Create a new point shapefile (or geodatabase featureclass) named Geometric Design within ArcCatalog with the same projection as the unzipped layers above.

Within an ArcMap project, add the following:

- · nhdflowline layer;
- Geometric Design layer;
- catchment shapefile;
- the FlowlineAttributesFlow table.

Add the following fields to the nhdflowline layer:

- LENGTHMi (type: double, precision: 9, scale 4)
- DrainMi (type: double, precision: 9, scale 4)
- MinElev (type: double, precision: 9, scale 4)
- MaxElev (type: double, precision: 9, scale 4)
- Gradient (type: double, precision: 9, scale 4)

Add the following field to the GeometricDesign layer (use the add field-batch tool):

- Geometric (type: double, precision: 5, scale 2)
- Lat (type: double, precision: 8, scale 5)
- Long (type: double, precision: 8, scale 5)
- COMID (type: long, precision: 9)

Join the nhdflowline layer with the FlowlineAttributesFlow table based on the COMID field.

Use the field calculator within the nhdflowline attribute table, with the appropriate metric to imperial conversion to populate the following fields:

• LENGTHMi (from LENGTHKM – kilometers to miles)

Date: January 6, 2015

- DrainMia (from CumDrainage square kilometers to square miles (sq mi))
- MinElev (from MinElevSmo meters to feet)
- MaxElev (from MaxElevSmo meters to feet)
- Gradient ((MaxElev-MinElev)/LENGTHMI).

Unjoin the FlowlineAttributesFlow table.

Label the "nhdflowline" layer based new "LengthMi" field – note: this field shows the cumulative drainage at the *end* of the line segment, which is rarely more than 2-3 miles in between nodes.

Calculate the geometric break points (i.e., for a 500 sq mi watershed: 500, 250, 125, 62.5, 31, 15, 7, 4, 2).

It is recommended to change the symbology (Symbology: Show Quantities: Classification (Manual)) of the actual flowline to reflect the drainage. This will help identify when and where sites need to be allocated.

Start a new editing session, with the GeometricDesign layer as your target layer.

Add a new point within this layer to the pour point for the watershed (500 sq mi in this case).

Travel upstream through the mainstem and "find" the next place on the stream where the river drainage brackets 250 sq mi. Use the catchment shapefile layer to identify more precisely the drainage value if needed.

Populate the "Geometric" field within the GeometricDesign layer accordingly to the identified drainage level, then change the symbology (Symbology: Categories: Unique Values: Geometric field) of this layer to reflect the drainage levels.

Proceed through the watershed (either around the outer portions or start with largest values and work in), adding points accordingly to each geometric level. Change the symbology to find areas or levels that were missed. Note – the drainage level must be exact. Use the catchment shapefile to subtract drainage areas from larger drainage areas until the exact drainage level is reached. It is ok to "skip" a geometric level if it is not exactly reached. Sometimes there are large tributaries whose contribution to the mainstem skips a drainage level.

Populate the COMID (manually), and Lat/Long (right click on field and select calculate geometry – lat = x-coordinates and long = y-coordinates) accordingly for reference within the Geometric Design Layer

Once sites are selected in this fashion, they will need to be snapped to a bridge or access point.

Additional sites should be placed at pour points of subwatersheds (12-digit HUCs) to meet TMDL document requirements.

Once the initial sites are selected, the following features are taken into account to move or add sites:

- Permitted facilities
- Urban areas
- Historical sampling sites
- Assessment Unit IDs (AUID)
- External stakeholder information
- Resources maximum of 35 sites per project

Date: January 6, 2015

After refining site selections, there may be additional sites added to ensure spatial representation of the project area.

Sites may be removed or changed after site reconnaissance if there are problems accessing the site or if sites are dry.

Notes regarding the NHD dataset:

All units are initially set to metric and need to be converted to imperial.

Within the nhdflowline layer, the GNIS_Name/ID refers to the whole river name and ID, while the COMID is a unique identifier for the particular segment.

There is *not* a value GNIS_Name/ID for every river, especially where primary streams and ditches are concerned.

Segments within the nhdflowline layer are based on linear miles between "nodes," which are broken up (typically) by tributary. Typically these lengths are less than 2-3 miles.

The cumulative drainage values in the NHD dataset have been compared against other and deemed "reasonable" (read – not statistically compared). Also note that the drainage is calculated through the model to be at the pour point of that segment.

The elevation values, however, are **not** reliable and require supervision. These values are calculated from the associated digital elevation model (DEM) and sometimes have null values for either the maximum or minimum elevation values. In addition, the length of the stream is not long enough (i.e. >1 mile) to calculate gradient. In either case, this associated value is helpful to identify contour changes against a USGS contour map. However, to note the calculated gradient from the NHD information has been observed to be within several tenths of mile compared to a manual calculation of gradient.

Important tables from NHD

- FlowlineAttributesFlow (found in: Region 05, Version 01_02, Catchment Flowline Attributes)
 - Key fields: CumDrainag, Max ElevRaw, MinElevSmo,

Important Layers from NHD

- Region 05, Version 01_01, Catchment Shapefile
- Region 05, Version 01_02, National Hydrography Dataset

Attachment 2. IDEM Site Reconnaissance Form.

		Site	Reconnaissa	nce Form	EPA Site lo	entifier	Rank
	-111				Recon #: Trlp #:		
ne Number:	Ĺ		Stream:		County:		
ocation Descrip	ption:						
	Reconnaissa	ince Data Collects	ed	Lando	wner/Contact In	formation	
_F	Recon Date	Crew I	Members	First Name	Last	Name	
Avg. Width A	lvg. Depth (m)	Max. Depth (m)	Nearest Town	Street A ddress	- 1 2 -		
GANAMAN A		auscoures -					
Water Present?	Site Wadeable?	Present?	Road/Public Access Possible?	City		State	Zip
☐ Site impacted by	, 0				192		
Livestock?	Control Con	diment? Gau	ge Present?	Telephone	E-I	Mail Addres	is
			П	Pamphlet Distributed?	Please Call In Advance?	Resu Reques	1907
			Rating, Results, Comm	ents, and Planning			
ine Rating By C 1=easy, 10=diff		Reconnaissan	ce Decision	Equipment Se	elected	Circle Eq.	uipment
Access Route		Pre-Recon Recon in proce	66			Backpack	
		Approved Site No. Landowner	denied access			Boat	
Safety Fa	actor	No, Dry No, Stream cha No, Physical ba	annel missing			Totebarge Longline	•
	6	No, Impounded	stream			Scanoe	
Sampling	Епоп		land e or not accessible e to traffic or location			Seine Weighted	Handlin
			ed by backwater			Waders Gill Net	
•					1980		
Comments							

Attachment 3: Blank Stream Sampling Field Data Sheet

\Box	-	\mathbf{v}	S	tr	ean	. 9	amn	lii	na Fi	eld	חו	at	a S	heet	Analysis	Set#	ı	EPA St	e ID	Ra	ink
		Ш			can		ναιτιρ		ıgı	CIC		aı	<u> </u>	HOUL			<u> </u>			<u> </u>	
Sample 1	*		Site	#				5	Sample M	lediun	n			Sa	тріе Туре		Dup	olicate	Samp	nie #	
	_										_			-			_				
Stream Nan		_									_	RIV	er Mile:			Coun	ny:				
Site Descript		Sample	Colle	ctor	18		Sample	Coll	lected	Lh	udroli	ah	٧	Water	Water Flo		low			Amu	uatic
Survey Crew Chief	1	2	3	_	4		Date	T	Time	۳,	/droi:	aD	Deptr	NGage Hi (ft)	(cf/sec		mate	d? Al	gae?		197
			Т	\exists	\neg			T		Т				1-7				\top		7	
	ole Ta					lquo		Ĺ		er Flo	_	•			ater Appeara		\Box	Cano			
☐ Yes ☐ No; Stream		No; Fi		8	1 2 8 8		3 🛮 4 12 🗆 24			Dry Run]sta]Fie	_	☐ Clear ☐ Murky	☐ Green ☐ Black	☐ Sheen ☐ Other		0-209 20-40			
☐ No; Owner							A8-Flow			Eddy] of		Brown	Gray (Sep			40-80			
Special Notes:																					
NOUSS.																					
Field Data	a:			_																	
Date (m/d/yy)		r Time :mm)	D.O (mg	_	pН		Vater mp (°C)		c Cond	Turbi (NT		%	sat.	Chiorine (mg/l)	Chloride (mg/l)	Chloro (mg				WS	
Comments	⊢		П	\neg			$\overline{}$						$\overline{}$					$\overline{}$	Т	г	г
Comments	上			_									_					_			
Comments	┡																				Щ
Comments	Н			П			Т					Г	Т					Т	П	П	Г
Comments	\vdash			_														_			
Comments	⊢			_								<u> </u>								_	щ
Comments						_					\neg				Weather Cod	ie Defini	tions	3			_
					ement	>	> Max. I	Viete	Measuren r Measurer	ment	ŀ		SC		WD			ws		A	_
				Flag	js	R			ee Comme ee Comme		-1	Sk	y Cond		Wind Dire	ction	Win	d Stre	ngth		
Field Cali	brat	ions				_					╗	1 Ck 2 Sc	ear attered	8 Rain 9 Snow	00 North (0 de 09 East (90 de		0C	alm ght		1<3	
Date	Tin		Calibra		_		Callb	_				3 Pa 4 Ck		10 Sleet	18 South (180 27 West (270 o	degrees)		od./Ligh		3 46- 4 61-	
(m/d/yy)	(hh:	mm)	initia	18	Тур	10	Meter	#	Value	Uni	18	5 Mil 6 Fo	st					lod./Stro trong	ng	576- 6>8	
											╛	7 Sh	ower				6 G	ale			
		\dashv						\Box			\Box						Ш				
		I Co	llbrat	lon	pН			_			_	_					Ш				
		Ľ	Туре		DO Turbidi	y															
Preservat						_		_			Г			: Preserv				ottie T			
Group: Pre	Bervat	tive F	Preser	vati	ve Lot	# E	lottle Typ	0	Bottle L	ot#	GC Nx	Ni	utrients:		e	2000P 1000P	1000r	nL Plast	ic, Na	TOW M	louth
		\dashv		_		+		+			CN	C	etals: HM yanide: M	HOEN		250P	250m	L Plastic L Plastic	, Nam	ow Mo	uth
		\dashv				+		+			Tox	cs To	na Grea naics: Ice acteriolog				500m	L Glass, L Glass, L Glass,	Wide	Mouth	1
											WOM	. W		rganics: HC	& Thiosulfate	125G	125m	L Glass, L Glass V Glass V	Wide		
												ı Pı	henois: H	12804		120PB 1000PF	120m	Plastic	(Back		
											Gly Hg	GI	yphosat	e: Thiosulfa 631): HCl	ite	500PF	500m				
											Cr6	CI	hromlum	VI(1636): N rcury(1630		250T	250m	L Teflon L Teflon			
													Lugi Mc		p. 4 man	125T		L Teflon			
Data Entered	IBy:_				Q	C1:										lea Eloid					

Attachment 4: Fish Collection Data Sheet

Event ID_ Voltage	Time	Voucher jars fished (sec)	Unknown jars Distance fished (m)	Equipment Max_depth (m)	nent x. depth (m)			Page of Avg. depth (m)					
Avg. widt	h (m)	Bridge in reach	_ Is reach representative_	If no, why									
Elapsed ti	me at site (hh	n:mm):Cor	mments										
	Museur	n data: Initials	ID date	lar count F	ish Tot	al				_			
Coding for			ed fins L – lesions T – tumor N						C-le	eche:			
W – swirle	d scales Y – po	peye S – emaciated F	– fungus P – parasites) H – he	avy L – light (these codes ma	y be co	mbine	d with a	above o	odes)				
TOTA	# OF FISH	(mass g)	WEIGHT (s)	(length mm)			ANON	MALIES	6				
		(111228)		Min length	D	Е	L	Т	М	0			
		┦											
				Max length									
v	Р												
-				Min length	D	Е	L	Т	М	0			
				Max length									
V	P												
				Min length	D	Е	L	Т	М	0			
				Max length									
V	Р			Wax Icrigati									
<u> </u>				Min length	D	E	L	Т	М	0			
v	Р			Max length									
v	P			Min length	_	_		_					
		 			D	Е	L	Т	М	0			
				Max length									
V	Р												
				Min length	D	Е	L	Т	М	0			
		1 1	1 1	Max length	1		I	I	1	1			

Attachment 5: Macroinvertebrate Header Form.



Office of Water Quality: Macroinvertebrate Header

L-Site #	Event ID	Stream N	ame	Location	n	County	Surveyor
Sample Date Sa	mple # N	Macro# # Co	ntainers		Kick	□ Normal □ Duplicate _	
☐ Habitat Comple	te 🗆 Sample	e Quality Rejecte	ł	☐ CPOM ☐ Hester-Dendy	□ MHAB □ Qualitative	Replicate _	
<u>Riparian Zo</u>	ne/Instre	am Feature	<u>s</u>			_	
Watershed Erosi ☐ Heavy ☐ Moderate ☐ None		Watershed NPS I No Evidence Obvious Sources Some Potential So					
Stream Depth Riffle (m):	Stream Depth Run (m):	Stream Depth Pool (m):		Distances Riffle-Riffle (m):	Distance Bend-Bend		
Stream Width (n	n): High V	Water Mark (m):	Velocity	(ft/s):			
Stream Type: Cold Warm	Turbidity Clear Opaque	y (Est): Slightly Turbio Turbid		y (mg/L): (ORP (mV):		
☐ Channelization	n 🗆 Dam P	resent	_				
Predominant Sur Other	rounding Lan	nd Use: 🗆 Forest	□ Field/Pastu	re 🗆 Agricultural 🗆	3 Residential	☐ Commercial ☐	Industrial
<u>Sediment</u>							
Sediment Odors:		_					
Sediment Deposi Sediment Oils:	_			nd □ Relic Shells O	ther		
☐ Are the undersid			-	l, black?			
			•				
Substrate C	omponen	ts					
(Note: Select from 0%							
Inorgan Boulder		conents (% Diameter Gravel Sand	Clay	Detritus	Detritus	te Components (% T Muck/Mud	ype) Marl(gray w/
Bedrock (>10 in)		.1-2.5 in) (gritty)	Silt (slick)	(sticks, wood)	(CPOM)	(black, fine FPOM)	shell fragments)
				J			
Water Quali	_	rana 🏻 Datrolaum	Chemical	□ None Other			
Water Odors: Water Surface O		_					

IDEM 03/14/13

Attachment 6: Biological Samples Field Chain-of-custody Form

IDEM	•	ВІ	OLO		NVII OF BIOL	RONME FICE OF OGICA	DEPARTM NTAL MAN F WATER Q AL STUDIES ES FIELD (NAGEM QUALIT S SECTION	ENT Y ON	DY		
I certify that the samp	le(s) listed below t						ce. Da	ate:/_ mple Type:	_/			
Signature:								impie Type: e. fish, macro	o, algae)			
EVENT ID (YY)/		2000 mL Nalgere	Nagene	SE S	lype (ADorAS)	(mL)	COLLEC	TED	PLACED IN S	TORAGE	200m#	Check line for sample present and accounted
MACRO # (9 DIGIT)	IDEM SAMPLE # (AB)	2000mI	250mL Nagane	125mLGtass	Type (A	Volume (mL)	Date (mm/dd/yyyy)	Time (24 hr)	Date (mm/dd/yyyy)	Time (24 hr)	StrageRoom#	for! One check per bottle.
								:		:		
								:		:		
								:		:		
								:		:		
								:		:		
								:		:		
								:		:		
								:		:		
								:		:		
								:		:		
								:		:		
								:		:		
								:		:		
								:		:		
								:		:		
								:		:		
								:		:		
								:		:		
								:		:		
								:		:		
								:		:		
								:		:		
								:		:		
	SIGNA	TUR	E			•	DATE A		Comments:			
RELINQUISHE							/	/	7			
RECEIVED BY:							:					
RELINQUISHEI							/	/				
RECEIVED BY:							:					
I certify that I received locked in a secure area Signature:		e(s) and	is/are :	recorde	d in the (b Custodian rd book. The same Date: /		l be in custody of c	ompetent lab	oratory per	sonnel at all times or
Lab: Indiana Depar	tment of Environ	nment	al Mar	nagem	ent I	Address	2525 N. Shadela					
The second second			erasla									

Attachment 7: Blank OWQ Biological Studies QHEI (Qualitative Habitat Evaluation Index) form (front)

IDEM		OWQ Bio	logical QHE	(Qualitat	ive Habitat	Evaluation	n Index)		
	Sample #		bioSample #	Stre	am Name		Location		
1	Surveyor	Sample Date	County	Macro Si	ample Type	☐ Habitat			
			,			Complete	QHEI So	ore:	
1] 50	IBSTRATE C	heck ONLY Two pr			;	Charl ONE (0-20		
	BEST TYPE		check every type p OT	resent HER TYPES	OR	IGIN	Or 2 & average) QUA	LITY	
PREDOMIN P/G R/R	ANT	PRESENT TOTAL % P/G R/R	PREDOMINANT P/G R/R	PRESENT TO P/G R/R		STONE[1]	s□ HEAW	[-2]	
	ldr/slabs[1/ Oulder[9]	0] === ===	☐☐ HARDPAN		ПШS	[1] ANDS[0]	ĭ□ MODE	RATE[-1]	Substrate
	OBBLE [8]		□□ MUCK[2]	., 00 _	□ HARD	PAN[o]	FREE [
□□ G	ravel[7] And[6]	H		AL[0] == -		STONE[0] VAP[0]	EXTEN	SIVE [-2]	l l
□□ B	edročík[5]		(Score natu	ral substrates; i		TRÜNÉ [0]	□ MODE	ATE[-1]	الصل
NUMB	EK UF BEST	TYPES: □ 4 or □ 3 or		from point-sour		: [-1] FINES [-2]	□ NORM		Maximum 20
21 7N		VER Indicate pre	seance 0 to 3 and	actimata narran	- 0_Abcont- 1_W	ary email amoun	te or if more come	oon of maro	inal
quality;	Moderate am	ounts, but not of h	ighest quality or in	small amounts	of highest quality	; 3-Highest	A	MOUNT	
		preater amounts (e loped root wad in o						E(Or2&av IVE>75 9	
% Amour	nt		% Amount		Amount		_ □ MODER/	ATE 25 - 75	5% [7]
		G VEĞETATION [1	ROOT	5 > 70am [2] _ WADS [1] _		Backwaters[Macrophytes	[1] □ SPARSE [1] □ NEARLY	5-<25% ABSENT <	
	SHALLOWS (II ROOTMATS [1	nslowwater)[]	1] BOUL	DERS[1]	LOGSORV	WOODY DEBRIS	[1]	Cover Maximum	
Comn	-	•						20	Щ
		RPHOLOGY α	eck ONE in each o	ateopry (Or 2.8	average)				
	OSITY	DEVELO	PMENT	CHANNELI NONE[6]		STAB □ HIG	ILITY		
	DERATE[3]	□ G0000	5]	□ RECOVERE		□ MO	Derate [2]	Channel	
□ NON		□ FAIR [3 □ POOR [☐ RECOVERI ☐ RECENTO	NG [3] RNORECOMERY	LOV [1]	V[1]	Maximum 20	1 1
Comm									
4] BAI	NK EROSIC	ON AND RIPA	RIAN ZONE (I	eck ONE in each	h category for EA	CH BANK (Or 2 p		e)	
L R	EROSION		>50m[4]		T, SWAMP[3]	ALIII	LR □□ CONSERVA	ALLET MOLETA	¥GE[1]
	ione/little[3 100 er ate[2]		RATE 10-50m[3] DW 5-10m[2]		BOROLD FIELD Ential, Park, N		□□ URBANOR □□ MONONG/(
	EAW/SEVERE	[1] VERY	NARROW[1]		D PASTURE [1]	Indica	ate predominant la	nd use(s)	m
		- NONE	[U]	LL UPBN	PASTURE, ROW	MUDP[U] Past	100m riparian.	Riparian Maximum	
51 PO		AND RIFFLE/	RUN OUALIT	Y				10	
MAX	IMUM DEP	TH CHAŃ	NEL WIDTH	•	CURRENT V			reation Pote	
	ONE (ONLY!) • 1m[6]		E (Or 2 & average) DTH > RIFFLE WI	DTH[2] □ 1	Check ALL th TORRENTIAL [-1]			e and comme Primary Cont	
	.7-<1m[4] .4-<0.7m[2]		DTH=RIFFLEWI DTH <rifflewi< td=""><td>DTH[1] 🗆 \</td><td>/ERYFAST[1] FAST[1]</td><td>□ INTERSTI □ INTERMI</td><td></td><td>Secondary O Pool/</td><td></td></rifflewi<>	DTH[1] 🗆 \	/ERYFAST[1] FAST[1]	□ INTERSTI □ INTERMI		Secondary O Pool/	
□ 0	2-<0.4m[1]		DIII < NOTE NO	., 🗆 1	Moděráte[1]	□ EDDIES[1	ι] ΄΄	Current	
Comm	:0.2m[0] [me ients	tnc=0j		I	ndicate for reach	- pools and riffle	·s.	Maximum 12	\Box
	ate for function fle-obligate spe	al riffles; Best area cies:	s must be large er	ough to suppor		O- 2 8	□ NORT	TLE [metric	=01
RIFF	LE DEPTH	RUN D			IN SUBSTRA	Or 2 & average) TE RIFFL	E/RUN EMBE		
		m[2] □ MAXII om[1] □ MAXII					NONE[2]	Riffle/	
	TAREAS<5a	n .	Soznijaj		(e.g., Fine Grave	Sand)[0]] Mod ěr áte[0]	Run	
Comm	ents "	ic=0]					DEXTENSIVE [-1	J Maximum 8	Ш
6] <i>GR</i> .	ADIENT (ft/mi)	 □ VERY LOW □ MODERATE 		%POOL:(── %GL	IDE:	Gradient Maximum	
DR	AINAGEA	REA (mi²)	THE RESERVE AND A SECOND		%RUN: (%RI	FFLE:	10	
								1	DEM 11/15/12

Attachment 7 (continued). IDEM OWQ Biological QHEI (back).

IDEM			owo	Q Biological	QHEI (Qualit	ative Hal	oitat Evaluation Index)	
1	COMMENT							
A-CANOPY	<u> </u>	B-AESTHETI	cs		C-RECREA	TION	D-MAINTENANCE	E-ISSUES
□ >85%-0	Open .	☐ Nuisancealga	e □ Oils	heen	Area	Depth	□Public □Private	□WWTP □CSO □NPDES
□ 55%-<8	85%	□ Invasive mad	rophytes 🗆 Tras	sh/Litter	Pool: □ > 100 ft ²	□ >3ft	□Active □ Historic	□ Industry □ Urban
□ 30%-<5	55%	□ Excess turbid	ity □ Nuis	sanceodor			Succession: □ Young □ Old	☐ Hardened ☐ Dirt & Grime
□ 10%-<3	30%	□ Discoloration	□ Sluc	lge deposits			□Spray □ Islands □ Scoured	□ Contaminated □ Landfill
□ <10%-(Closed	□ Foam/Soum	□ C90	0s/990s/Outfalls			Snag: □ Removed □ Modified	BMPs: □ Construction □ Sedimer
							Leveed: □One sided □Both banks	□ Logging □ Irrigation □ Cooling
Lookingupstear		ings≤10m,1 readin					□ Relocated □ Cutoffs	Erosion: □ Bank □ Surface
	Right	Middle	Left	Total Averag	je		Bedload: □ Moving □ Stable	□ False bank □ Manure □ Lagox
%open	%	%	%	%			□ Armoured □ Slumps	□WashH₂O□Tile□H₂OTable
							□ Impounded □ Desiccated	Mine: □ Acid □ Quarry
	\ /	\ /	\ /				□ Flood control □ Drainage	Flow: □ Natural □ Stagnant
	\sim	\sim	\sim					□ Wetland □ Park □ Golf
								□ Lawn □ Home
	,	,	,					☐ Atmospheric deposition
								□ Agriculture □ Livestock
Stream D	rawing:							

IDEM 11/15/12

Attachment 8: Chain-of-custody Form

OWO Chain of Custody Form											т.	roject: eam:	unto Poé-		
I Certify th	at the sample(s) II:	sted b	elow w	38/We	re col	lected	i by m	10, OF	in my	ргөзе	ence.		Date:	WQ Analy	/818 Set:
Signature:													Section		
Lab											Time				
Assigned Number	Control Number	ξĒ	ID	₽	100	, 5	120 G-18	8 Z	동급			Date	9	Time	1
]
													\Box		
		L						_	_	_			_		4
		L				<u> </u>		L	_	<u> </u>			\rightarrow		4
		⊢	<u> </u>		H	H		H	H	⊢		_	\rightarrow		-
		Н	<u> </u>		H	H		H	H	H		_	\rightarrow		-
		\vdash	\vdash	\vdash	\vdash	\vdash	\vdash	\vdash	\vdash	\vdash	\vdash		\dashv		-
		\vdash	\vdash		\vdash	\vdash		\vdash	\vdash	\vdash			\dashv		1
		\vdash				Н		\vdash		\vdash			\dashv		1
		Т				Т			\vdash	\vdash			\dashv		1
		П				П							\neg		1
]
													_		
					_	_		_	_	_			\rightarrow		4
		L	<u> </u>			L		L	L	L			\rightarrow		-
		H	<u> </u>		H	H		⊢	H	⊢		<u> </u>	\dashv		-
			_			H		H	H	H			\dashv		-
		\vdash				\vdash		\vdash	\vdash	\vdash			\dashv		-
		\vdash				\vdash				\vdash			\dashv		1
		\vdash				Т							\dashv		1
		Т				П		П	Т	Т			\neg		1
]
]
P = Plastic	G = Glass		ı	N. M. =	- Narr	ow M		Ţ		ct = B	acteri	ological	Only	Shou	ild samples be iced? Y N
I certify that I have	received the abov	e sam	ple(8).				C	arrie	rs						
		ature						T	Dat	9	1	Tme	Seal	s Intact	Comments
Relinquished By:								4			l		Y	N	
Received By: Relinquished By:								+			┡		Ŀ.		
Received By:								-			l		Υ	N	
Relinquished By:								+			⊢				
Received By:								\dashv					Y	N	
						ave b		ecord			ficial	record b	ook. Ti	ne same s	ample(s) will be in the custody
Signature:											Date:			т	lme:
Lab:						Ac	idress	B:							

Date: January 6, 2015

Attachment 9: Sample Analysis Request form.



Indiana Department of Environmental Management
Office of Water Quality
Water had Street and Accessorate Bases in

Watershed Planning and Assessment Branch www.idem.IN.gov

Water Sample Analysis Request

65-00-V	Project Nam	e:	Composite 🗆	Grab ⊠
OWQ Sample Set	1	IDEM Sample Nos.		
Crew Chief		Lab Sample Nos.		
Collection Date		Lab Delivery Date		

Anions and Physical Parameters									
Parameter	Test Method	Total	Dissolved						
Alkalinity (as CaCO₀)	EPA 310.2	⊠ **							
Total Solids	SM 2540B	≥ **							
Suspended Solids	SM 2540D	⊠ **							
Dissolved Solids	SM 2540C		⊗ **						
Sulfate	EPA 375.2	⊠ **	□ **						
Chloride	SM 4500CI-E	⊗ **							
Hardness (as CaCO ₂)	EPA 130.1	× **							
Fluoride	380-75WE	□ **							
Silica (Reactive)	SM 4500-SiD	□ **							

Priority Pollutant Metals Water Parameters			
Parameter	Test Method	Total	Dissolved
Antimony	200.8		
Arsenic	200.8		
Beryllium	200.8		
Cadmium	200.8		
Chromium (Hex)	SM 3500Cr-D		
Chromium (Total)	200.8		
Copper	200.8		
Lead	200.8		
Mercury,	EPA 245.1		
Nickel	200.8		
Selenium	200.8		
Silver	200.8		
Thallium	200.8		
Zinc	200.7		

Cations and Secondary Metals Parameters			
Parameter	Test Method	Total	Dissolved
Aluminum	200.7, 200.8		
Barium	200.8		
Boron	200.8		
Calcium	200.7, 200.8	×**	
Calcium (as CaCO ₃)	SM 3500Ca-D		
Cobalt	200.8		
Iron	200.7		
Magnesium	200.7, 200.8	×**	
Manganese	200.8		
Potassium	SM 3500-K D		
Sodium	200.7		
Strontium	200.7		

Send reports (Fed. Ex. or UPS) to: Deliver reports to:

David Jordan - IDEM Mail Code 65-40-2 (Shadeland) 100 N. Senate Ave. Indianapolis, IN 46204-2251 David Jordan - IDEM STE 100 2525 North Shadeland Ave. Indianapolis, IN 46219 DJordan@idem.in.gov

Organic Water Parameters			
Parameter	lest Method	lotal	
Priority Pollutants: Oranochlorine Pesticides and PCBs	EPA 608	-	
Polynuclear Aromatic Hydrocarbons	EPA 610		
Priority Pollutants: VOCs - Purgeable Organics	EPA 624		
Priority Pollutants: Base/Neutral Extractables	EPA 625		
Priority Pollutants: Acid Extractables	EPA 625		
Phenolics, 4AAP	EPA 420.4		
Oil and Grease, Total	EPA 1664A		
Semi-volatile Organics & Pesticides	EPA 525.2		

Nutrient & Organic Water Chemistry Parameters			
Parameter	Test Method	Total	Dissolved
Ammonia Nitrogen	EPA 350.1	8	
CBOD;	SM 5210B		
CBODu	SM 5210B		
Total Kjeldahl Nitrogen (TKN)	EPA 351.2	⊠	
Nitrate + Nitrite	EPA 353.1	8	
Dissolved Reactive Phosphorus	SM4500-P		
Total Phosphorus	EPA 365.1	8	
TOC	SM 5310B	8	
COD (Low Level)	SM 5220D		
Cyanide (Total)	EPA 335.4		
Cyanide (Free)	SM 4500CN-I	_ *	
Cyanide (Amenable)	SM 4500CN-G	_ *	

Bacteriological Water Parameters			
Parameter	Test Method	Total	Dissolved
E. coli (Colilert Method)	SM9223B		

30 day reporting time required.

Notes:

** = DO NOT RUN PARAMETER IF SAMPLE
IDENTIFIED AS A BLANK ON THE CHAIN OF
CUSTODY

* = RUN ONLY IF TOTAL CYANIDE IS DETECTED

*** = Report Calcium, Magnesium as Total Hardness components if Hardness is calculated

Testing Laboratory: Indiana State Departs

Indiana State Department of Health (ISDH) Environmental Laboratory Division

550 W. 16th Street Indianapolis, IN 46202

Phone: 317-921-5815 (Ray Beebe) (Rev. 6/2013)